



Specifications:

Output

Output power capacity	3,000 VA
Output power capacity	2,250 Watts
Output Voltage	120 V
Output Connections	(8)NEMA 5-15R
Optional AC Connection	There are optional AC Connections.
Waveform type	Sinewave
Transfer time	2ms typical

Input

Nominal input voltage	120 V
Input frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input connection	NEMA L5-30P

Batteries

Typical backup time at half load	18.1 minutes
Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	5 hour(s)
Replacement battery cartridge	(1) RBC11

Communications & Management

Interface port	RS-232 communications port; Smart-Slot card expansion slot(s) for feature expansion
Management Software included	PowerChute Smart-UPS Bundle
Optional Software	There are other software options.
Control panel	LED status display with load and battery bar-graphs and On Line : On Battery : Replace Battery : and Overload Indicators

Audible alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency Power Off (EPO) Optional Management Device	Optional There are several Management Devices.

Surge Protection and Filtering

Surge energy rating (Joules)	320
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical

Maximum height dimensions	
Maximum width dimensions	
Maximum depth dimensions	
Rack Height	5 U
Net weight	
Shipping weight	
Color	Biege

Environmental

Operating environment	0-40 degrees C (32-104 F) : 0-95% Relative Humidity : 0-3000 meters elevation (0-10000 ft)
Storage conditions	-15 - 45 degrees C (32-120 F) : 0-95% Relative Humidity : 0-15000 meters elevation (0-50000 ft)
Audible noise at 1 meter from surface of unit	53 dBA
Online thermal dissipation	375 BTU/hr

Conformance

Approvals	CSA; FCC A; UL 1778
Standard warranty	2 years repair or replace, optional on-site warranties available, optional extended warranties available

Optional Service	There are other service options.
------------------	----------------------------------