

Advanced, Feature-Rich, Multi-Line IP Phone for Business or a Home Office

Stylish and functional in design, the SPA942 IP Phone is ideal for a residence or business using a hosted IP telephony service, an IP PBX, or a large scale IP Centrex deployment. The SPA942 leverages industry-leading VoIP technology from Linksys to deliver an upgradeable high-quality IP Phone that is unparalleled in features, value, and support.

Based on the SIP standard, the SPA942 has been tested to ensure comprehensive interoperability with equipment from VoIP infrastructure leaders, enabling service providers to quickly roll out competitive, feature-rich services to their customers.

With hundreds of features and configurable service parameters, the SPA942 addresses the requirements of traditional business users while leveraging the advantages of IP telephony. Features such as easy station moves, presence, and shared line appearances (across local and geographically-dispersed locations) are just some of the many advantages.

Standard features on the SPA942 include two active lines, dual-switched Ethernet ports, 802.3af Power Over Ethernet (PoE)* support, a high-resolution graphical display, full-duplex speakerphone, and a 2.5 mm headset port. With a simple software update, the SPA942 is upgradeable to a four-line phone. Each line can be independently configured to use a unique phone number (or extension), or can be configured to use a shared number that is assigned to multiple phones.

The SPA942 uses standard encryption protocols to provide secure remote provisioning and unobtrusive in-service software upgrades. Linksys secure remote provisioning tools include detailed performance measurement and troubleshooting features, enabling network providers to deliver high-quality support to their subscribers. Remote provisioning also saves service providers the hassle and expense of managing, preloading, and re-configuring customer premise equipment (CPE).

*The power supply for the SPA942 is sold separately and is required if PoE functionality is not implemented.

Connect directly to an Internet Telephone Service Provider or connect to an IP PBX

Dual-switched Ethernet ports, full-duplex speakerphone, caller ID, call hold, conferencing, and more

Easy installation and secure remote provisioning— menu-based and web-based configuration.

Comprehensive interoperability and SIP-Based feature set



SPA942

PRODUCT DATA

BUSINESS SERIES

IP Phone

Model: **SPA942**

IP Phone

Specifications

Model SPA942

Hardware

Pixel-Based Display—128 x 64 Monochrome Graphical Liquid Crystal Display (LCD)
Four Illuminated Call Appearance Line Buttons with Tricolor LEDs
LED Indicates Line State—Active, Idle, On-Hold, Unregistered
Line LED Configurable to 13 Different States (On/Off, Color, Flash)
Dedicated Illuminated On/Off Buttons for Audio Mute, Headset, and Speakerphone
Four Soft Key Buttons
Four Way-Rocking Directional Button for Menu Navigation
Support for up to two attached Attendant Consoles; adds up to 64 programmable buttons
Voice Mail Message Waiting Indicator Light
Voice Mail Message Retrieval Button
Dedicated Hold Button
Settings Button for Access to Feature, Set-up, and Configuration Menus
Volume Control Rocking Up/Down Button Controls Handset, Headset, Speaker, Ringer
Standard 12-Button Dialing Pad
High-Quality Handset (RJ-7 connector) and Cradle
Built-In High Quality Microphone and Full-Duplex Speakerphone
Headset Jack—2.5 millimeter port
LED Test Function
Two Ethernet LAN Ports with Integrated Ethernet Switch – 100BaseT RJ-45
802.3af Compliant Power over Ethernet (PoE)
Optional 5 volt DC Universal (100-240 Volt) Switching (Power Supply is Ordered Separately)

Security

Password-Protected System, Preset to Factory Default
Password-Protected Access to Administrator and User Level Features
HTTPS with Factory-Installed Client Certificate
HTTP Digest—Encrypted Authentication via MD5 (RFC 1321)
Up to 256-bit AES Encryption

Documentation

Installation and Configuration Guide
User Guide
Administration Guide
Provisioning Guide—For Service Providers Only

Environmental

Dimensions	7.68" x 6.3" x 7.09" (195 x 160 x 180 mm)
Weight	2.15 lb (0.9752 kg)
Power	DC Input Voltage: +5 Volts DC at 2.0 Amps Maximum Power Consumption: 5 Watts Switching Type (100-240v) Automatic Optional Power Adapter (models PA100-NA, PA100-EU, PA100-UK, PA100-AU): 100-240v - 50-60Hz (26-34VA) AC Input
Certification	FCC (Part 15, Class B), CE, A-Tick, ICES-003
Operating Temp.	32 to 113°F (0 to 45°C)
Storage Temp.	-13 to 185°F (-25 to 85°C)
Operating Humidity	10 to 90%, Noncondensing
Storage Humidity	10 to 90%, Noncondensing

Package Contents

- 1 SPA942 IP Phone, Handset, and Stand
 - 1 Handset Cord
 - 1 RJ-45 Ethernet Cable
 - 1 Quick Installation Guide
- (Optional Power Supply is Ordered Separately)

PRODUCT DATA

BUSINESS SERIES

Functions and Features

Up to Four Lines with Independent Configuration and Registration—ships with two lines enabled. A two-line upgrade is available via a software license key installed locally using the web interface, or installed remotely via a secure profile update.

Line Status—Active Line Indication, Name and Number

Menu-Driven User Interface—Multiple Languages Supported

Digits Dialed with Number Auto-Completion

Shared Line Appearance**

Full-Duplex Speakerphone

Call Hold

Music on Hold**

Call Waiting

Caller ID Name and Number

Outbound Caller ID Blocking

Call Transfer—Attended and Blind

Call Conferencing

Automatic Redial

On-Hook Dialing

Call Pick Up—Selective and Group**

Call Park and Retrieval**

Call Swap

Call Back on Busy

Call Blocking—Anonymous and Selective

Call Forwarding—Unconditional, No Answer, On Busy

Hot Line and Warm Line Automatic Calling

Call Logs (60 entries each)—Made, Answered, and Missed Calls

Redial from Call Logs

Personal Directory with Auto-dial (100 entries)

Do Not Disturb (callers hear line busy tone)

URI (IP) Dialing Support (Vanity Numbers)

On-Hook Default Audio Configuration (Speakerphone and Headset)

Multiple Ring Tones with Selectable Ring Tone per Line

Called Number with Directory Name Matching

Call Number using Name—Directory Matching or via Caller ID

Subsequent Incoming Calls with Calling Name and Number

Date and Time with Intelligent Daylight Savings Support

Call Duration and Start Time Stored in Call Logs

Call Timer

Name and Identity (Text) Displayed at Start Up

Distinctive Ringing Based on Calling and Called Number

Ten User-Downloadable Ring Tones—Free Ring Tone Generator from www.linksys.com

Speed Dialing

Configurable Dial/Numbering Plan Support (per line)

Intercom** and Group Paging**

DNS SRV and Multiple A Records for Proxy Lookup and Proxy Redundancy

Syslog and Debug Server Records (Configurable Per Line)

Report Generation and Event Logging

Statistics Transmitted in BYE Message

Secure Call Encrypted Voice Communication Support - SIP over TLS, and SRTP

Built-in Web Server for Administration and Configuration with Multiple Security Levels

Automated Provisioning, Multiple Methods—up to 256 Bit Encryption (HTTP, HTTPS, TFTP)

Asynchronous Notification of Upgrade Availability via NOTIFY

Non-intrusive, In-Service Upgrades

Optionally Require Admin Password to Reset Unit to factory Defaults

** Feature requires support by SIP server

PRODUCT DATA

BUSINESS SERIES

Data Networking

MAC Address	(IEEE 802.3)
IPv4	Internet Protocol v4 (RFC 791), upgradeable to v6 (RFC 1883)
ARP	Address Resolution Protocol
DNS	A Record (RFC 1706), SRV Record (RFC 2782)
DHCP Client	Dynamic Host Configuration Protocol (RFC 2131)
ICMP	Internet Control Message Protocol (RFC792)
TCP	Transmission Control Protocol (RFC793)
UDP	User Datagram Protocol (RFC768)
RTP	Real Time Protocol (RFC 1889) (RFC 1890)
RTCP	Real Time Control Protocol (RFC 1889)
DiffServ	(RFC 2475)
Type of Service-TOS	(RFC 791/1349)
VLAN Tagging 802.1p/q	Layer 2 QoS
SNTP	Simple Network Time Protocol (RFC 2030)

Voice

SIPv2—Session Initiation Protocol Version 2 (RFC 3261, 3262, 3263, 3264)
SIP Proxy Redundancy—Dynamic via DNS SRV, A Records
Re-registration with Primary SIP Proxy Server
SIP Support in Network Address Translation Networks—NAT (including STUN)
SIPFrag (RFC 3420)
Secure (Encrypted) Calling via Pre-Standard Implementation of Secure RTP
Codec Name Assignment
Voice Algorithms:
G.711 (A-law and μ -law, G.726 (16/24/32/40 kbps), G.729 A, G.723.1 (6.3 kbps, 5.3 kbps)
Dynamic Payload Support
Adjustable Audio Frames Per Packet
DTMF—In-band and Out-of-Band (RFC 2833) (SIP INFO)
Flexible Dial Plan Support with Inter-Digit Timers
IP Address/URI Dialing Support
Call Progress Tone Generation
Jitter Buffer—Adaptive
Frame Loss Concealment
VAD—Voice Activity Detection with Silence Suppression
Attenuation/Gain Adjustments
MWI—Message Waiting Indicator Tones
VMWI—Voice Mail Waiting Indicator—Via NOTIFY, SUBSCRIBE
Caller ID Support (Name and Number)
Third Party Call Control (RFC 3725)

Linksys Phone Comparison Chart

Model	Voice Lines	Ethernet Ports	High-Resolution Graphical Display	Power over Ethernet Support
SPA901	1	1	No	No
SPA921	1	1	Yes	No
SPA922	1	2	Yes	Yes
SPA941	2 to 4	1	Yes	No
SPA942	2 to 4	2	Yes	Yes
SPA962	6	2	Yes, Color	Yes

Check the product package and contents for specific features supported. Specifications are subject to change without notice.



Linksys is a registered trademark or trademark of Cisco Systems, Inc. and/or its affiliates in the U.S. and certain other countries. Copyright © 2008 Cisco Systems, Inc. All rights reserved. Other brands and product names are trademarks or registered trademarks of their respective holders.

Linksys
A Division of Cisco Systems, Inc.
121 Theory
Irvine, CA 92617 USA

E-mail: sales@linksys.com
Web: www.linksys.com

Linksys products are available in more than 50 countries, supported by 12 Linksys Regional Offices throughout the world. For a complete list of local Linksys Sales and Technical Support contacts, visit our worldwide website at www.linksys.com

PRODUCT DATA

BUSINESS SERIES

LINKSYS[®]
A Division of Cisco

8022020NC-KO

Model: **SPA942**