



TE2000

The TE2000® series boasts business level performance with its long battery life, and improved versatility via a flexible expansion bay - all built brilliantly into an impressive and stylish easy to carry lightweight chassis. With integrated wireless networking plus a wide choice of mainstream configurations, the TE2000® is engineered to be your perfect partner for business in the new world.

Toshiba PCs use genuine Microsoft® Windows®
<http://www.microsoft.com/piracy/howtotell>

MODEL	CPU	MEMORY	DISPLAY	HDD	DRIVE	Modem/LAN	Wifi(802.11b)	OS
TE2000	PIII 1000MHz	128MB	14.1" XGA TFT	20GB	DVD	Integrated Modem and LAN	Integrated Antenna	Win 98
TE2000	PIII 1000MHz	128MB	14.1" XGA TFT	20GB	DVD	Integrated Modem and LAN	Integrated Antenna	Win 2K/Win XP Pro
TE2000	PIII 1133MHz	256MB	14.1" XGA TFT	20GB	DVD	Integrated Modem and LAN	Integrated Antenna	Win 98
TE2000	PIII 1133MHz	256MB	14.1" XGA TFT	20GB	DVD	Integrated Modem and LAN	Integrated Antenna	Win 2K/Win XP Pro
TE2000	PIII 1200MHz	256MB	14.1" XGA TFT	30GB	DVD/CDRW	Integrated Modem and LAN	Integrated Antenna	Win 98
TE2000	PIII 1200MHz	256MB	14.1" XGA TFT	30GB	DVD/CDRW	Integrated Modem and LAN	Integrated Antenna	Win 2K/Win XP Pro

Business Professional Performance

- Choice of mainstream configurations meeting all business requirements at popular price points

Easy to Deploy and Manage

- Single software image
- Integrated asset tag - MAC address and serial number for easy tracking of assets
- Common docking, Slim SelectBay™ accessories and other accessories with Tecra 9000 and Portege 4000^{AA}
- Managed price transitions

Flexible Expandable and Portable Design

- Thin and Light from 2.4kg
- Up to 6 hours battery life*
- Excellent desktop expansion
- The Slim SelectBay™ allows you to double storage capacity or extend battery life with a range of innovative accessories including DVD-ROM, DVD/CDRW, second battery or hard disk drive.

Convenient and reliable connectivity

- Secure wireless access to corporate network with integrated wireless antenna (802.11b)
- Integrated LAN
- Integrated Modem

Outstanding Ease of Use

- Fast boot, fast reliable resume
- Hot swappable integrated Slim SelectBay™
- Port replicator options
- Convenient and reliable connectivity including wireless capabilities
- Light and thin with up to 6 hours battery life*
- Accupoint®

It's a whole new world out there.

TOSHIBA



TE2000



Integrated stereo speakers



Select Bay™ easy expansion capability



Curved avant-garde design



TE2000® Series

Processor

Mobile Intel® Pentium® III processor -M
1000MHz/1133MHz/1200MHz with integrated 512KB on-die
Level 2 cache
133MHz processor system bus

System Architecture

PCI Bus V2.2

Hard Disk

20GB** or 30GB**
Accommodates 9.5mm height, 2.5" hard drives
12-14ms average access time (read/write)
2.5-3ms track-to-track seek time (read/write)
Enhanced IDE (ATA-5)
User removable

Memory

Capacity: up to 512MB† (1GB** Ready)
Type: 128MB or 256MB PC133 SDRAM 3.3V
Expandable with two user installable memory slots
(One slot used by standard memory)

BIOS

ACPI, PnP, SM BIOS

Colour Display

TFT active-matrix colour display
XGA 1024 x 768
14.1" diagonal: up to 16 million colours

Video

Cyber ALADiN-T™ graphics controller, 128-bit
16MB external UMA video memory
3D graphics accelerator
BitBLT hardware
AGP 66MHz bus

External CRT Support

16M colours:
1024 x 768, 800 x 600, 640 x 480 @ 60/75/85Hz non-interlaced
64K colours:
1600 x 1200 @ 60/non-interlaced
1280 x 1024 @ 60/75/85Hz non-interlaced

Diskette Drive (Bundled)

External USB FDD 3.5", 1.44MB

Slim SelectBay™ DVD-ROM[‡] (Bundled or Optional)

5.25" EIDE, 8X max. DVD-ROM,
12.7mm height
100ms DVD-ROM random access time
Compatibility: CD-ROM, CD-R (read only), CD-RW (read only),
DVD-ROM, DVD-R (read only)
Internal use in Hot Swappable Slim SelectBay™

Slim SelectBay™ CD-RW/DVD-ROM Drive (Bundled or Optional)

5.25" EIDE, 8X max. CD-R, 4X max. CD-RW, 24X max.
CD-ROM, 8X MAX. DVD-ROM; 12.7mm height
180ms DVD-ROM average maximum transfer rate
130ms CD-ROM average maximum transfer rate
Compatibility: CD-ROM, CD-R (read/write), CD-RW
(read/re-write), DVD-ROM, DVD-R (read only)
Internal use in Hot Swappable Slim SelectBay™

Slim SelectBay™ Second Battery (Optional)^{††}

Lithium Ion, (10.8V, 3000mAh)
Internal use in Hot Swappable Slim SelectBay™
Additional 3 hour battery life

Slim SelectBay™ Second HDD (Optional)

30GB** enhanced IDE (ATA-5)
Internal use in Hot Swappable Slim SelectBay™

Audio

M1535B PCI bus sound chip
Sound Blaster® Pro compatible
16-bit stereo
3D Sound support
DirectSound® DirectSound3D®
Full duplex sound support
Headphone and microphone ports
Integrated stereo speakers

Expansion

Two PC Card slots support two Type II or one Type III PC Cards
Supports PCMCIA R2.01, PC Card 16, CardBus ready
One Hot Swappable Slim SelectBay™
One free expansion memory slot
SVGA video port
TV-out port (NTSC/PAL output; RCA jack)
ECP parallel port
High-speed serial port (16550 UART compatible)
PS/2® mouse/keyboard port
Fast infrared port (4Mbps, IrDA V1.1 compliant)
Two Universal Serial Bus (USB V1.1) ports
RJ-11 modem port
RJ-45 LAN port
240-pin expansion bus for connection to optional
Advanced Port Replicator
Shutter door covering selected ports when not in use
Optional Advanced Port Replicator

Optional Advanced Port Replicator

Built in RJ-11 modem port
Built in RJ-45 10/100 networking ethernet port
One 9-pin (RS-232C/16550 UART) serial port
2 x USB ports
Parallel printer port
Connector for external SVGA display
P/S 2® mouse/keyboard port
Line in & Line out jack
DC Power in
 Kensington lock slot
AC adapter & Australian 240V power cord

Communications

Integrated V.90 56K modem¹
Integrated Intel® 10/100 Base-TX Ethernet
Integrated Wi-Fi™ Antenna (802.11b)
Optional Integrated Wi-Fi™ Mini PCI Card (802.11b)

Battery

Rechargeable, removable Lithium Ion battery (10.8V, 3600mAh)
Up to 6 hours battery life^{††}
Up to 3.3 hours battery life with main battery, 6 hours with
second battery^{††}
4 hours recharge time
ACPI support

Power Supply

75W external AC adapter
100-240V input voltage
50-60Hz frequency

Keyboard

Full-sized 85 keys
Integrated AccuPoint® II pointing device, scroll
function-programmable

Dimensions (h x w x d)

34/38mm (front/back) x 316mm x 275mm[‡]

Weight

Configurable from 2.4Kg (with weight saver)
Configurable from 2.7Kg (with DVD)

Security

HDD access password (Supplied on request)
SecureSleep™
 Kensington Cable lock slot
Optional Fingerprint Reader PC card: security at Bios level,
BootLock, BioLogon, Bioshield Functions, Keyboard lock

Environmental Specifications

Temperature:

Operating: 5° to 35° C (41° to 95° F)
Non-operating: -20° to 65° C (-4° to 149° F)

Thermal gradient:

Operating: 15° C per hour maximum
Non-operating: 20° C per hour maximum

Relative Humidity:

Operating: 20% to 80% non-condensing
Non-operating: 10% to 90% non-condensing

Shock:

Operating: 7G, 1.5G with CD/DVD-ROM
Non-operating: 60G

Vibration:

Operating: 0.2G, 0.25G with CD/DVD-ROM
Non-operating: IG

Software

Microsoft® Windows 98SE or Microsoft® Windows 2000, Windows
XP-Pro, Toshiba Windows Media Player Skin, Intervideo™, WinDVD
Online documentation
Toshiba Management Console and Toshiba Console
Software may differ depending on configuration ordered.
Please confirm or check configuration requirements with your
Toshiba Authorised Reseller

Warranty

1-year parts and labor domestic and international warranty
(Terms and conditions apply, see www.isd.toshiba.com.au or
your Toshiba reseller for details)
Domestic warranty includes free courier pick up and return service

Featured Part Numbers

PT200A-00JYT	(PIII-M 1000MHz, 14.1" TFT XGA, 128MB, 20GB, DVD, Modem, LAN, Wireless LAN Antenna Win98SE)
PT200A-00JVW	(PIII-M 1000MHz, 14.1" TFT XGA, 128MB, 20GB, DVD, Modem, LAN, Wireless LAN Antenna Win2K/WinXP Pro)
PT200A-00WUT	(PIII-M 1133MHz, 14.1" TFT XGA, 256MB, 20GB, DVD, Modem, LAN, Wireless LAN Antenna, Win98SE)
PT200A-00WUW	(PIII-M 1133MHz, 14.1" TFT XGA, 256MB, 20GB, DVD, Modem, LAN, Wireless LAN Antenna, Win2K/WinXP Pro)
PT200A-0188T	(PIII-M 1200MHz, 14.1" TFT XGA, 256MB, 30GB, DVD/CDRW, Modem, LAN, Wireless LAN Antenna, Win98SE)
PT200A-0188W	(PIII-M 1200MHz, 14.1" TFT XGA, 256MB, 30GB, DVD/CDRW, Modem, LAN, Wireless LAN Antenna, Win2K/WinXP Pro)

Accessories

KTT-SO133/128I	Kingston™ PC133 128Mb Memory module
KTT-SO133/256I	Kingston™ PC133 256Mb Memory module
KTT-SO133/512I	Kingston™ PC133 512Mb Memory module
PA3083E-1ACA	Universal AC adapter
PA3128U-1BAS	Battery Pack
PA3129U-1BAS	Slim SelectBay™ 2nd Battery Pack
PA3091E-1CHG	Battery Recharger
PA3082U-1PRP	Advanced Port Replicator 2001
PA3134U-1ETC	Slim SelectBay™ HDD adapter
PA3116U-1H30	30GB HDD Kit (requires PA3134U-1ETC)
PA3137A-1CD2	Slim SelectBay™ CD-RW/DVD-ROM Drive Kit
PA3109U-1FDD	USB FDD Kit
PA3140U-1PCC	Wireless LAN PC Card (WEP128)
PA3065U-1ETC	Wireless LAN access point
PA3070U-6MPC	Wireless LAN Mini-PCI Card Kit (WEP 128)
PA3066U-1PCC	PC Card Fingerprint Reader
KENS64020	Slim MicroSaver™ Security lock with 2 keys
DEFCON Lock	Defcon™ Cable Security with combination lock
DEFCON1	Personal Security device
NWUNSMS	Wave Grey monitor stand
PA350/Tosh	Auto/Air adapter
NWMSSUP	Silver USB Mini-Mouse with Trackball
NWMOSSU	Silver USB Mini-Mouse with Optical
PA060U	Black mini USB Hub
CARRYALL	Toshiba Dobby Oxford Carry Bag
SLIMLINE	Toshiba Slimline Koskin Carry Bag
COMMUTER	Toshiba Dobby Oxford Travel Carry Bag
CLASSIC	Toshiba Leather Carry Bag
LEATHER B/CASE	Toshiba Executive Leather Briefcase
EASY ROLLER	Carry Bag with wheels and extended handle

Please direct all enquiries to:



Toshiba PCs use genuine Microsoft® Windows®
<http://www.microsoft.com/piracy/howtotell>

Toshiba (Australia) Pty. Limited ACN 001 320 421 NB. * Long life battery with second battery. **GB means 1 billion bytes. †MB means 1 million bytes. ††Colour varies between TE2000 and Tecra 9000/Portege 4000 (Actual data transmission speeds vary depending on line conditions. †††Battery life may vary depending on configuration, applications, power management settings and features utilised. Recharge time varies depending on usage. Battery may not charge while computer is consuming full power. †Thickness may vary at certain points on the system. ††††On selected models only. Toshiba accepts no responsibility for errors in specifications, typography or photography, please consult your Toshiba reseller to confirm specifications. †††††(820Kbps (DVD-ROM); 3,600Kbps (CD-ROM) maximum data transfer rate. Specifications subject to change without notice. Trademarks as indicated are registered trademarks and are the property of the respective owners. Battery is eligible for 12 months domestic warranty only. Toshiba Australia Information Systems Division 2002.

TOSHIBA