

Rack PDU, Basic, Zero U, 20A, 208V, (20)C13 & (4)C19

AP7540

Overview

Lead time Usually in Stock

Main

Color	Black
Product or Component Type	PDU
PDU Type	Basic
Cord length	10 ft (3.05 m)
Number of cables	1
Provided Equipment	Installation guide Rack Mounting brackets Toolless Mounting Kit

Complementary

Input Voltage	200 V 208 V 230 V
Height	63.74 in (161.9 cm)
Width	2.20 in (5.6 cm)
Output Voltage	208 V
Depth	1.73 in (4.4 cm)
Net Weight	10.71 lb(US) (4.86 kg)
Mounting Location	Side
Mounting preference	No preference
Input Plug Type	NEMA L6-20P
Mounting Mode	Rack-mounted
Rack units	OU
Mounting position	Vertical
Line Rated Current	16 A
Input current limits	20 A
Load Capacity	3300 VA
Input Frequency	50/60 Hz
Outlet type and quantity	20 IEC 60320 C13 4 IEC 60320 C19

Environment

Product Certifications	cUL Listed UL Listed
Standards	CSA C22.2 No. 60950-1-03 UL 60950-1
Ambient Air Temperature for Operation	32113 °F (045 °C)
Relative Humidity	595 %
Operating altitude	010000 ft
Ambient Air Temperature for Storage	-13149 °F (-2565 °C)
Storage Relative Humidity	595 %
Storage altitude	050000 ft (0.000000000015240.0000000000 m)

Ordering and shipping details

Category	80230-IG SEBA TO SEUSA	
Discount Schedule	BMS1	
GTIN	731304207931	
Returnability	No	
Country of origin	IN	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	84.02 in (213.4 cm)
Package 1 Width	5.00 in (12.7 cm)
Package 1 Length	5.98 in (15.2 cm)
Package 1 Weight	12.72 lb(US) (5.77 kg)

Contractual warranty

Warranty 2 years repair or replace

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

⊘ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	120
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
☼ Energy efficiency	
Optimized Energy Efficiency	Energy efficient product

Use Again

◯ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	Yes

Product data sheet

AP7540

Image of product / Alternate images

Alternative





Jan 9, 2025

