# Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

### Rack PDU, Metered, 1U, 16A, 208/230V, (8) C13



AP7821B

#### **Overview**

Lead time Usually in Stock	
----------------------------	--

#### Main

Product or Component Type	PDU
PDU Type	Metered
Cord length	8.2 ft (2.5 m)
Provided Equipment	Cord retention bracket(s) Installation guide Rack Mounting brackets User Manual

#### Complementary

Input Voltage	200 V
	208 V
	230 V
Height	1.73 in (4.4 cm)
Width	17.48 in (44.4 cm)
Output Voltage	208 V
	230 V
Depth	4.02 in (10.2 cm)
Net Weight	3.84 lb(US) (1.74 kg)
Mounting Location	Front
	Rear
Mounting preference	No preference
Input Plug Type	IEC 60320 C20
Mounting Mode	Rack-mounted
Rack units	1U
Mounting position	Horizontal
Line Rated Current	16 A
Input current limits	20 A
Load Capacity	3300 VA
Input Frequency	50/60 Hz
Outlet type and quantity	8 IEC 60320 C13

#### **Environment**



B 1 10 15 15		
Product Certifications	cUL Listed	
	C-tick	
	CE	
	CSA	
	GOST	
	UL Listed	
	VCCI	
	VDE	
Standards	FCC Part 15 class A	
	ICES-003	
	UL 60950	
Ambient Air Temperature for Operation	23113 °F (-545 °C)	
Relative Humidity	595 %	
Operating altitude	010000 ft	
Ambient Air Temperature for Storage	-13149 °F (-2565 °C)	
Storage Relative Humidity	595 %	
Storage altitude	050000 ft (0.000000000015240.0000000000 m)	

#### Ordering and shipping details

GTIN	731304331513
Country of origin	IN

#### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.52 in (6.4 cm)
Package 1 Width	13.27 in (33.7 cm)
Package 1 Length	18.50 in (47 cm)
Package 1 Weight	6.44 lb(US) (2.92 kg)

#### **Contractual warranty**

Warranty 2 years repair or replace

#### **Environmental Data**

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Carbon footprint (kg CO2 eq, Total Life cycle)	4308
Environmental Disclosure	Product Environmental Profile

#### **Use Better**

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	1cdb2fed- a06f-4574-913d-8df8e70936b2
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
☼ Energy efficiency	
Optimized Energy Efficiency	Energy efficient product

#### **Use Again**

## Circularity Profile End of Life Information Removable battery Yes Take-back Yes

#### Product data sheet

AP7821B

Image of product / Alternate images

**Alternative** 







