

# Product data sheet

Specifications



## Rack PDU 2G, Switched, ZeroU, 20A/208V, 16A/230V, (7) C13 & (1) C19

AP8958

### Overview

**Presentation** APC Switched Rack Power Distribution Units (PDUs) enable advanced, user-customizable power control and active monitoring. Remote outlet level controls allow power on/off functionality for power recycling to remotely reboot equipment and restrict unauthorized use of individual outlets. Power sequencing delays allow users to define the order in which to power up or down attached equipment. Avoid circuit overload during power recovery and extend uptime of critical equipment by prioritizing the load shedding. Current metering provides real-time remote monitoring of connected loads. Switched Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and low profile circuit breakers. User-defined alarms warn of potential circuit overloads before critical IT failures occur. Users can access, configure, and control Switched Rack PDUs through secure Web, SNMP, or Telnet Interfaces and is complimented by APC Centralized Management platforms using InfraStruxure Central, Capacity Manager and Change Manager.

**Lead time** Usually in Stock

### Main

**Color** Black

**Product or Component Type** PDU

**PDU Type** Switched

**Provided Equipment** Installation guide  
Rack Mounting brackets  
Serial configuration cable  
Safety guide

### Complementary

**Input Voltage** 200 V  
208 V  
230 V

**Height** 38.90 in (98.8 cm)

**Width** 2.20 in (5.6 cm)

**Output Voltage** 100 V  
200 V  
208 V  
230 V

**Depth** 1.81 in (4.6 cm)

**Net Weight** 7.12 lb(US) (3.23 kg)

**Mounting Location** Side

**Mounting preference** No preference

**Input Plug Type** IEC 60320 C20

**Mounting Mode** Not rack-mountable

**Rack units** 0U

Mounting position	Vertical
Line Rated Current	16 A
Acceptable Input Voltage	100...240 V
Input current limits	20 A
Load Capacity	3300 VA
Input Frequency	50/60 Hz
Outlet type and quantity	7 IEC 60320 C13 1 IEC 60320 C19

## Environment

Product Certifications	cUL Listed PSE UL Listed VCCI Class A VDE
Standards	EN 55022 Class A EN 55024 EN 61000-3-2 EN 61000-3-3 FCC Part 15 class A ICES-003
Ambient Air Temperature for Operation	23...140 °F (-5...60 °C)
Relative Humidity	5...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)

## Ordering and shipping details

GTIN	731304277101
Country of origin	IN

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	44.29 in (112.5 cm)
Package 1 Width	6.50 in (16.5 cm)
Package 1 Length	4.49 in (11.4 cm)
Package 1 Weight	10.49 lb(US) (4.76 kg)

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle)	<b>1302</b>
------------------------------------------------	-------------

Environmental Disclosure	<a href="#">Product Environmental Profile</a>
--------------------------	-----------------------------------------------

## Use Better

### Materials and Substances

Packaging made with recycled cardboard	<b>Yes</b>
----------------------------------------	------------

Packaging without single use plastic	<b>No</b>
--------------------------------------	-----------

EU RoHS Directive	<b>Compliant with Exemptions</b>
-------------------	----------------------------------

SCIP Number	<b>1cdb2fed-a06f-4574-913d-8df8e70936b2</b>
-------------	---------------------------------------------

REACH Regulation	<a href="#">REACH Declaration</a>
------------------	-----------------------------------

### Energy efficiency

Optimized Energy Efficiency	<b>Energy efficient product</b>
-----------------------------	---------------------------------

## Use Again

### Repack and remanufacture

Circularity Profile	<a href="#">End of Life Information</a>
---------------------	-----------------------------------------

Removable battery	<b>Yes</b>
-------------------	------------

WEEE



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

---

Take-back

Yes

---

Image of product / Alternate images

Alternative

---

