

Product data sheet

Specifications



APC Rack PDU 9000 Switched, ZeroU, 20A, 208V, (21) C13/C15 & (3) C19/C21, L620 Cord

APDU9959NA3

Overview

Lead time Usually in Stock

Main

Color Black

Product or Component Type PDU

PDU Type Switched

Provided Equipment Installation guide
Rack Mounting brackets
Safety guide

Complementary

Input Voltage 200 V
208 V

Height 70.75 in (179.7 cm)

Width 2.17 in (5.5 cm)

Output Voltage 208 V
200 V

Depth 1.81 in (4.6 cm)

Net Weight 12.37 lb(US) (5.61 kg)

Mounting Location Side

Mounting preference No preference

Input Plug Type IEC 60320 L6-20P

Mounting Mode Not rack-mountable

Rack units 0U

USB compatible No

Mounting position Vertical

Communication Port Protocol SNMP
Redfish

Line Rated Current 16 A

Acceptable Input Voltage 100...240 V

Input current limits 20 A

Load Capacity 3300 VA

Input Frequency 50/60 Hz

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Outlet type and quantity	21C13/C15 3C19/C21
Communication Network Type	10/100/1000BASE-T

Environment

Product Certifications	cUL Listed FCC part 15 class A PSE
Standards	IEC 62368-1
Ambient Air Temperature for Operation	23...140 °F (-5...60 °C)
Relative Humidity	5...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)

Ordering and shipping details

GTIN	731304356301
-------------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	78.82 in (200.2 cm)
Package 1 Width	4.49 in (11.4 cm)
Package 1 Length	6.50 in (16.5 cm)
Package 1 Weight	17.33 lb(US) (7.86 kg)

Contractual warranty

Warranty	3 years repair or replace
-----------------	---------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle)	2259
--	-------------

Environmental Disclosure	Product Environmental Profile
--------------------------	---

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
--	------------

Packaging without single use plastic	No
--------------------------------------	-----------

EU RoHS Directive	Compliant with Exemptions
-------------------	----------------------------------

SCIP Number	31346aed-552c-4a16-81d9-e683a383b6da
-------------	---

REACH Regulation	REACH Declaration
------------------	-----------------------------------

China RoHS Regulation	China RoHS declaration
-----------------------	--

Use Again

Repack and remanufacture

Circularity Profile	End of Life Information
---------------------	---

Removable battery	Yes
-------------------	------------

WEEE



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Take-back

No

Image of product / Alternate images

Alternative

