

Product data sheet

Specifications

Rack ATS, 200/208V, 30A, L6-30 in, (16) C13 (2) C19 out



AP4432

⚠ Discontinued on: Jun 9, 2023

⚠ Discontinued

Overview

Lead time Usually in Stock

Main

Main Input Voltage	200 V 208 V
Main Output Voltage	200 V 208 V
Input Connection Type	NEMA L6-30P
Number of rack unit	2U
Cable length	8 ft (2.4 m)
Number of cables	2
Provided Equipment	Mounting Hardware Rack Mounting brackets RS-232 configuration cable

Physical

Height	3.46 in (8.8 cm)
Width	17.01 in (43.2 cm)
Depth	9.29 in (23.6 cm)
Net Weight	14.51 lb(US) (6.58 kg)
Mounting Location	Front Rear
Mounting preference	No preference
Mounting Mode	Rack-mounted

Input

Input Frequency	50/60 Hz
Line Rated Current	24 A
Max line current	30 A
Input current limits	30 A
Load Capacity	4992 VA

Output

Max current draw 30 A

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number of power socket outlets	16 IEC 60320 C13
	2 IEC 60320 C19
Protection Type	Circuit breaker

Conformance

Product Certifications	PSE
	TÜV-C
	TÜV-NURTL
Standards	EN 55022 Class A
	FCC Part 15 class A

Environmental

Ambient Air Temperature for Operation	23...113 °F (-5...45 °C)
Relative Humidity	5...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)

Ordering and shipping details

GTIN	731304333463
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.27 in (21 cm)
Package 1 Width	14.02 in (35.6 cm)
Package 1 Length	22.99 in (58.4 cm)
Package 1 Weight	20.00 lb(US) (9.07 kg)

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better

Materials and Substances

EU RoHS Directive

Compliant with Exemptions

Use Again

Repack and remanufacture

Circularity Profile

[End of Life Information](#)

Image of product / Alternate images

Alternative

