



# AP7991

RoHS

★★★★★ (0) [Write a review](#)

Switched Rack Power Distribution Units (PDUs) provide advanced load monitoring combined with remote on/off switching control of individual outlets for power cycling ...

Includes: Rack Mounting Brackets, Toolless Mounting Kit

## Technical Specifications

### Output

Nominal Output Voltage	208V
Maximum Total Current Draw	16
Output Connections	(21) IEC 320 C13 (Battery Backup) (3) IEC 320 C19 (Battery Backup)

### Input

Nominal Input Voltage	208V 3PH
Input frequency	50/60 Hz
Input Connections	NEMA L21-20P
Cord Length	10ft (3.05meters)
Number of Power Cords	1
Load Capacity	5700VA
Maximum Input Current	20A
Regulatory Derated Input Current (North America)	16A

### Physical

Maximum Height	63.75inches (1619MM, 161.9CM)
Maximum Width	2.19inches (56MM, 5.6CM)
Maximum Depth	1.73inches (44MM, 4.4CM)
Net Weight	13.0lbs. (5.91KG)
Shipping weight	15.0lbs. (6.82KG)
Shipping Height	83.0inches (2108MM, 210.8CM)
Shipping Width	4.5inches (114MM, 11.4CM)
Shipping Depth	6.0inches (152MM, 15.2CM)
Color	Black

## Environmental

<b>Operating Temperature</b>	23 - 113 °F (-5 - 45 °C)
<b>Operating Relative Humidity</b>	5 - 95 %
<b>Operating Elevation</b>	0-10000ft (0-3000meters)
<b>Storage Temperature</b>	-25 - 65 °C
<b>Storage Relative Humidity</b>	5 - 95 %
<b>Storage Elevation</b>	0-50000ft (0-15000meters)

## Conformance

<b>Approvals</b>	cUL Listed, CSA, FCC Part 15 Class A, ICES-003, Industry Canada, UL 60950, UL Listed
<b>Standard warranty</b>	2 years repair or replace

## Sustainable Offer Status

<b>RoHS</b>	Compliant
<b>PEP</b>	Available in Documentation tab
<b>EOLI</b>	Available in Documentation tab

