



Share:



RACK PDU 2G, SWITCHED, ZEROU, 5.7KW, 200/208V, (21) C13 & (3) C19

AP8961

★★★★★
Be the first to [write a review](#)

Share this Product:



Description: APC Switched Rack Power Distribution

Units (PDUs) enable advanced, user-customizable power control and active monitoring. Remote outlet level controls allow power on/off functionality for power recycling to remotely reboot equipment and restrict unauthorized use of individual outlets. Power sequencing delays allow users to define the order in which to power up or down attached equipment. Avoid circuit overload during power recovery and extend uptime of critical equipment by prioritizing the load shedding. Current metering provides real-time remote monitoring of connected loads. Switched Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and low profile circuit breakers. User-defined alarms warn of potential circuit overloads before critical IT failures occur. Users can access, configure, and control Switched Rack PDUs through secure Web, SNMP, or Telnet Interfaces and is complimented by APC Centralized Management platforms using InfraStruxure Central, Capacity Manager and Change Manager.

Includes : Installation guide , Rack Mounting brackets , Safety guide , Serial configuration cable



Product Overview

Technical Specifications

Documentation

Software & Firmware

Options

Ratings & Reviews

Output

[Print Technical Specification](#)

Nominal Output Voltage	208V
Overload Protection	No
Maximum Total Current Draw	20
Output Connections	(3) IEC 320 C19 (Battery Backup) (21) IEC 320 C13 (Battery Backup)

Input

Nominal Input Voltage	208V 3PH
Input frequency	50/60 Hz
Input Connections	NEMA L21-20P
Cord Length	6ft (1.83meters)
Number of Power Cords	1
Maximum Input Current	20A
Maximum Line Current	20A
Regulatory Derated Input Current (North America)	16A

Physical

Maximum Height	70.5inches (1791mm , 179.1cm)
Maximum Width	2.2inches (56mm , 5.6cm)
Maximum Depth	1.82inches (46mm , 4.6cm)
Net Weight	15.2lbs. (6.91kg)
Shipping weight	19.4lbs. (8.82kg)
Shipping Height	78.8inches (2002mm , 200.2cm)
Shipping Width	6.5inches (165mm , 16.5cm)
Shipping Depth	4.5inches (114mm , 11.4cm)
Color	Black
Units per Pallet	48.0

Environmental



Operating Elevation	0-10000ft (0-3000meters)
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0-50000ft (0-15000meters)
Conformance	
Approvals	cUL Listed, FCC Part 15 Class A, ICES-003, UL Listed, VCCI Class A
Standard warranty	2 years repair or replace
Sustainable Offer Status	
RoHS	Compliant
REACH	REACH: Contains No SVHCs
PEP	Available in Documentation tab
EOLI	Available in Documentation tab
Battery Directive	Compliant
Battery Notes	ts_Battery_Notes



Sign up to stay up to date with best practices, new solutions and special offers.

Email

OK

WHO WE ARE

CONNECT WITH US

FIND A RESELLER

Zip/Postal Code

FIND

CATALOG KEYCODE

Enter Key Code

GO



TERMS & CONDITIONS >

PRIVACY STATEMENT >

© 2017, APC by Schneider Electric