

# Cisco Nexus 3016 Switch

## Product Overview

The Cisco Nexus<sup>®</sup> 3016 Switch (Figure 1) is a 40 Gigabit Ethernet switch platform. It is a high-performance, ultra-low-latency Ethernet switch providing line-rate Layer 2 and 3 switching in a compact one-rack-unit (1RU) form factor. The switch runs the industry-leading Cisco<sup>®</sup> NX-OS Software operating system, providing customers with robust features and functions that are widely deployed globally.

The line-rate Layer 2 and 3 switching at ultra-low latencies along with the serialization benefits of 40 Gigabit Ethernet switching make the Cisco Nexus 3016 an ideal switch platform for financial co-locations. This switch supports both forward and reversed airflow schemes with AC and DC power inputs.

**Figure 1.** Cisco Nexus 3016 Switch



## Main Benefits

The Cisco Nexus 3016 provides the following main benefits:

- Ultra-low latency
  - The Cisco Nexus 3016 delivers ultra-low nominal latency that enables customers to implement high-performance infrastructures for high-frequency trading workloads. Customers can also achieve faster application performance because of the serialization savings from switching at 40 Gigabit Ethernet speeds.
- Wire-rate Layer 2 and 3 switching on all ports
  - Layer 2 and 3 switching of up to 1.2 terabits per second (Tbps) and more than 950 million packets per second (mpps) is provided in a compact 1RU form-factor switch.
- Purpose-built on Cisco NX-OS operating system with comprehensive, proven innovations
  - Virtual PortChannel (vPC) provides Layer 2 multipathing through the elimination of Spanning Tree Protocol and enables fully utilized bisectional bandwidth and simplified Layer 2 logical topologies without the need to change the existing management and deployment models.
  - Power On Auto Provisioning (POAP) enables touchless bootup and configuration of the switch, drastically reducing provisioning time.
  - Cisco Embedded Event Manager (EEM) and Python scripting enable automation and remote operations in data center.
  - Advanced buffer monitoring reports real-time buffer utilization per port and per queue, which allows organizations to monitor traffic bursts and application traffic patterns.

- The 64-way equal-cost multipath (ECMP) routing enables Layer 3 fat tree designs and allows organizations to prevent network bottlenecks, increase resiliency, and add capacity with little network disruption.
- EtherAnalyzer is a built-in packet analyzer for monitoring and troubleshooting control-plane traffic and is based on the popular Wireshark open source network protocol analyzer.
- Precision Time Protocol (PTP; IEEE 1588) provides accurate clock synchronization and improved data correlation with network captures and system events.
- Full Layer 3 unicast and multicast routing protocol suites are supported, including Border Gateway Protocol (BGP), Open Shortest Path First (OSPF), Enhanced Interior Gateway Routing Protocol (EIGRP), Routing Information Protocol Version 2 (RIPv2), Protocol Independent Multicast sparse mode (PIM-SM), Source-Specific Multicast (SSM), and Multicast Source Discovery Protocol (MSDP).
- Network traffic monitoring with Cisco Nexus Data Broker
  - Build simple, scalable and cost-effective network tap or Cisco Switched Port Analyzer (SPAN) aggregation for network traffic monitoring and analysis.

## Configuration

- 16 fixed 40 Gigabit Ethernet Enhanced Quad Small Form-Factor Pluggable (QSFP+) ports (each QSFP+ port can handle four 10 Gigabit Ethernet connections)
- Locator LED
- Dual redundant power supplies
- Fan tray with redundant fans
- Two 10/100/1000-Mbps management ports
- One RS-232 serial console port
- One USB port
- Locator LED and button

Both forward (port-side exhaust) and reversed (port-side intake) airflow schemes are supported.

## Transceiver and Cabling Options

The Cisco Nexus 3016 has 16 QSFP+ ports. QSFP+ technology allows smooth transition from 10 to 40 Gigabit Ethernet infrastructure in data centers. Each of the Cisco Nexus 3016 Switch's QSFP+ ports can operate in either native 40 Gigabit Ethernet mode or 4 x 10 Gigabit Ethernet mode. This switch supports both fiber and copper cabling solutions for these two modes.

For low-cost cabling, copper-based 40-Gbps Twinax cables can be used, and for longer cable reaches, short-reach optical transceivers are excellent. Connectivity can be established from the QSFP ports to 10 Gigabit Ethernet switches or hosts using a splitter cable that has a QSFP transceiver on one end and four SFP+ transceivers on the other end. Similar capability can be achieved on the fiber solution by using QSFP+ SR4 transceivers on both ends and procuring third-party fiber splitter MPO-to-LC cables. Table 1 lists the QSFP transceiver types supported.

**Table 1.** Cisco Nexus 3016 QSFP Transceiver Support Matrix

Part Number	Description
QSFP-4SFP10G-CU5M	QSFP to 4xSFP10G Passive Copper Splitter Cable, 5m
QSFP-4SFP10G-CU3M	QSFP to 4xSFP10G Passive Copper Splitter Cable, 3m
QSFP-4SFP10G-CU1M	QSFP to 4xSFP10G Passive Copper Splitter Cable, 1m
QSFP-H40G-CU5M	40GBASE-CR4 Passive Copper Cable, 5m
QSFP-H40G-CU3M	40GBASE-CR4 Passive Copper Cable, 3m
QSFP-H40G-CU1M	40GBASE-CR4 Passive Copper Cable, 1m
QSFP-40G-SR4	40GBASE-SR4 QSFP Transceiver Module with MPO Connector

For more information about the transceiver types, see

[http://www.cisco.com/en/US/products/hw/modules/ps5455/prod\\_module\\_series\\_home.html](http://www.cisco.com/en/US/products/hw/modules/ps5455/prod_module_series_home.html).

### Cisco NX-OS Software Overview

Cisco NX-OS is a data center-class operating system built with modularity, resiliency, and serviceability at its foundation. Cisco NX-OS helps ensure continuous availability and sets the standard for mission-critical data center environments. The self-healing and highly modular design of Cisco NX-OS makes zero-impact operations a reality and enables exceptional operation flexibility.

Focused on the requirements of the data center, Cisco NX-OS provides a robust and comprehensive feature set that meets the networking requirements of present and future data centers. With an XML interface and a command-line interface (CLI) like that of Cisco IOS® Software, Cisco NX-OS provides state-of-the-art implementations of relevant networking standards as well as a variety of true data center-class Cisco innovations.

### Cisco NX-OS Software Benefits

Table 2 summarizes that benefits that Cisco NX-OS offers.

**Table 2.** Benefits of Cisco NX-OS Software

Feature	Benefit
<b>Common software throughout the data center: Cisco NX-OS runs on all Cisco data center switch platforms: Cisco Nexus 7000, 5000, 4000, and 1000V Series Switches and Cisco Nexus 2000 Series Fabric Extenders.</b>	<ul style="list-style-type: none"> <li>• Simplification of data center operating environment</li> <li>• End-to-end Cisco Nexus and Cisco NX-OS fabric</li> <li>• No retraining necessary for data center engineering and operations teams</li> </ul>
<b>Software compatibility: Cisco NX-OS interoperates with Cisco products running any variant of Cisco IOS Software and also with any networking OS that conforms to the networking standards listed as supported in this data sheet.</b>	<ul style="list-style-type: none"> <li>• Transparent operation with existing network infrastructure</li> <li>• Open standards</li> <li>• No compatibility concerns</li> </ul>
<b>Modular software design: Cisco NX-OS is designed to support distributed multithreaded processing. Cisco NX-OS modular processes are instantiated on demand, each in a separate protected memory space. Thus, processes are started and system resources allocated only when a feature is enabled. The modular processes are governed by a real-time preemptive scheduler that helps ensure timely processing of critical functions.</b>	<ul style="list-style-type: none"> <li>• Robust software</li> <li>• Fault tolerance</li> <li>• Increased scalability</li> <li>• Increased network availability</li> </ul>
<b>Troubleshooting and diagnostics: Cisco NX-OS is built with unique serviceability functions to enable network operators to take early action based on network trends and events, enhancing network planning and improving network operations center (NOC) and vendor response times. Cisco Smart Call Home and Cisco Online Health Management System (OHMS) are some of the features that enhance the serviceability of Cisco NX-OS.</b>	<ul style="list-style-type: none"> <li>• Quick problem isolation and resolution</li> <li>• Continuous system monitoring and proactive notifications</li> <li>• Improved productivity of operations teams</li> </ul>
<b>Ease of management: Cisco NX-OS provides a programmatic XML interface based on the NETCONF industry standard. The Cisco NX-OS XML interface provides a consistent API for devices. Cisco NX-OS also provides support for Simple Network Management Protocol (SNMP) Versions 1, 2, and 3 MIBs.</b>	<ul style="list-style-type: none"> <li>• Rapid development and creation of tools for enhanced management</li> <li>• Comprehensive SNMP MIB support for efficient remote monitoring</li> </ul>

Feature	Benefit
Using the Cisco Nexus Data Broker software and Cisco Plug-in for OpenFlow agent, the Cisco Nexus 3016 Switch can be used to build a scalable, cost-effective, and programmable tap or SPAN aggregation infrastructure. This approach replaces the traditional purpose-built matrix switches with these switches. You can interconnect these switches to build a multilayer topology for tap or SPAN aggregation infrastructure.	<ul style="list-style-type: none"> <li>• Scalable and cost effective</li> <li>• Robust traffic filtering capabilities</li> <li>• Traffic aggregation from multiple input ports across different switches</li> <li>• Traffic replication and forwarding to multiple monitoring tools</li> </ul>
Role-based access control (RBAC): With RBAC, Cisco NX-OS enables administrators to limit access to switch operations by assigning roles to users. Administrators can customize access and restrict it to the users who require it.	<ul style="list-style-type: none"> <li>• Tight access control mechanism based on user roles</li> <li>• Improved network device security</li> <li>• Reduction in network problems arising from human errors</li> </ul>

### Cisco NX-OS Software Packages for Cisco Nexus 3016

The Cisco NX-OS Software packages available with the Cisco Nexus 3016 offer flexibility and a comprehensive feature set as well as consistency with Cisco Nexus access switches. The default system software has a comprehensive Layer 2 feature set with robust security and management features. To enable Layer 3 IP unicast and multicast routing functions, additional licenses need to be installed. Table 3 summarizes the software packages.

**Table 3.** Cisco NX-OS Software Packages Available for Cisco Nexus 3016

Software	Description
<b>System default (no license required)</b>	<ul style="list-style-type: none"> <li>• Comprehensive Layer 2 feature set: VLAN, IEEE 802.1Q Trunking, Link Aggregation Control Protocol (LACP), vPC, Unidirectional Link Detection (UDLD) (standard and aggressive), Multiple Spanning Tree Protocol (MSTP), Rapid Spanning Tree Protocol (RSTP), Spanning Tree Protocol guards, and VLAN Trunking Protocol (VTP) transparent</li> <li>• Security: Authentication, authorization, and accounting (AAA); configurable Control-Plane Policing (CoPP); Dynamic Host Configuration Protocol (DHCP) snooping; storm control; and private VLAN (PVLAN)</li> <li>• Management features: IEEE 1588 (PTP) boundary clock, Cisco SPAN, Encapsulated Remote SPAN (ERSPAN), Cisco Data Center Networking Manager (DCNM) support, console, Secure Shell Version 2 (SSHv2) access, Cisco Discovery Protocol, SNMP, and syslog</li> </ul>
<b>Base license (N3K-BAS1K9)</b>	<ul style="list-style-type: none"> <li>• Layer 3 IP routing: Inter-VLAN routing (IVR), static routes, RIPv2, access control lists (ACLs), OSPFv2 (limited to 256 routes), EIGRP stub, Hot Standby Router Protocol (HSRP), Virtual Router Redundancy Protocol (VRRP), and Unicast Reverse Path Forwarding (uRPF)</li> <li>• Multicast: PIM-SM, SSM, and MSDP</li> </ul>
<b>LAN Enterprise license (N3K-LAN1K9)</b>	<ul style="list-style-type: none"> <li>• Advanced Layer 3 IP routing: OSPFv2, EIGRP, BGP, and Virtual Route Forwarding lite (VRF-lite)</li> </ul>
<b>Cisco Nexus Data Broker license (NDB-FX-SWT-K9)</b>	<ul style="list-style-type: none"> <li>• License for using the tap and SPAN aggregation functions with Cisco Nexus Data Broker; only the Base license is needed for this feature</li> </ul>

The Base license (N3K-BAS1K9) is required to take advantage of LAN Enterprise license (N3K-LAN1K9) features. Table 5 later in this document provides a complete feature list.

### Cisco Data Center Network Manager

The Cisco Nexus 3016 is supported in Cisco DCNM. Cisco DCNM is designed for hardware platforms enabled for Cisco NX-OS, which consist of the Cisco Nexus Family of products. Cisco DCNM is a Cisco management solution that increases overall data center infrastructure uptime and reliability, hence improving business continuity. Focused on the management requirements of the data center network, Cisco DCNM provides a robust framework and comprehensive feature set that meets the routing, switching, and storage administration needs of present and future data centers. In particular, Cisco DCNM automates the provisioning process, proactively monitors the LAN by detecting performance degradation, secures the network, and streamlines the diagnosis of dysfunctional network elements.

## Cisco Nexus Data Broker

The Cisco Nexus 3016 Switch with Cisco Nexus Data Broker can be used to build a scalable and cost-effective traffic monitoring infrastructure using network taps and SPAN. This approach replaces the traditional purpose-built matrix switches with one or more OpenFlow-enabled Cisco Nexus switches. You can interconnect these switches to build a scalable tap or SPAN aggregation infrastructure. You also can combine tap and SPAN sources to bring the copy of the production traffic to this tap or SPAN aggregation infrastructure. In addition, you can distribute these sources and traffic monitoring and analysis tools across multiple Cisco Nexus switches. For more details, visit <http://www.cisco.com/go/nexusdatabroker>.

## Product Specifications

Table 4 lists the specifications for the Cisco Nexus 3016, Table 5 lists software features, and Table 6 lists management standards and support.

**Table 4.** Specifications

Description	Specification	
<b>Physical</b>	<ul style="list-style-type: none"> <li>• 1RU fixed form-factor switch</li> <li>• 16 QSFP ports; each supports native 40 Gigabit Ethernet and 4 x 10 Gigabit Ethernet modes</li> <li>• 2 redundant power supplies</li> <li>• 1 fan tray with redundant fans</li> <li>• 1 I/O module with management, console, and USB flash memory ports</li> </ul>	
<b>Performance</b>	<ul style="list-style-type: none"> <li>• 1.28-Tbps switching capacity</li> <li>• Forwarding rate of 950 mpps</li> <li>• Line-rate traffic throughput (both Layer 2 and 3) on all ports</li> <li>• Configurable maximum transmission units (MTUs) of up to 9216 bytes (jumbo frames)</li> </ul>	
<b>Hardware tables and scalability</b>	MAC addresses	128,000
	Number of VLANs	4096
	Spanning-tree instances	<ul style="list-style-type: none"> <li>• RSTP: 512</li> <li>• MSTP: 64</li> </ul>
	Access control list (ACL) entries	2000 ingress 1000 egress
	Routing table	16,000 prefixes and 16000 host entries <sup>*</sup> 8000 multicast routes <sup>*</sup>
	Number of EtherChannels	64 (with vPC)
	Number of ports per EtherChannel	16
	Buffers	9 MB shared
	Boot flash memory	2 GB
<b>Power</b>	Frequency	50 to 60 Hz
	Power supply types	AC (forward and reversed airflow) DC (forward and reversed airflow)
	Typical operating power	172 watts (W; with Twinax at 100% load; 2 power supply units [PSUs]) 174W (with short-reach optics at 100% load; 2 PSUs)
	Maximum power	227W
	AC PSUs <ul style="list-style-type: none"> <li>• Input voltage</li> <li>• Frequency</li> <li>• Efficiency</li> </ul>	100 to 240 VAC 50 to 60 Hz 89 to 91% at 220V

Description	Specification
	DC PSUs <ul style="list-style-type: none"> <li>• Input voltage</li> <li>• Max current</li> <li>• Efficiency</li> </ul>
	Power supply efficiency
	Typical heat dissipation
	Maximum heat dissipation
<b>Cooling</b>	Forward and reversed airflow schemes Forward airflow: Port-side exhaust (air enters through fan tray and power supplies and exits through ports); supported with AC and DC power supplies Reversed airflow: Port-side intake (air enters through ports and exits through fan tray and power supplies); supported with AC power supply only Single fan tray with redundant fans Hot swappable (must swap within 1 minute)
<b>Sound</b>	Measured sound power (maximum) <ul style="list-style-type: none"> <li>• Fan speed: 40% duty cycle</li> <li>• Fan speed: 60% duty cycle</li> <li>• Fan speed: 100% duty cycle</li> </ul>
<b>Environment</b>	Dimensions (height x width x depth)
	Weight
	Operating temperature
	Storage temperature
	Operating relative humidity
	Storage relative humidity
	Altitude

\* Please refer to Cisco Nexus 3000 Series Verified Scalability Guide documentation for exact scalability numbers validated on specific software releases:  
[http://www.cisco.com/en/US/products/ps11541/products\\_installation\\_and\\_configuration\\_guides\\_list.html](http://www.cisco.com/en/US/products/ps11541/products_installation_and_configuration_guides_list.html).

**Table 5.** Software Features

Description	Specification
<b>Layer 2</b>	<ul style="list-style-type: none"> <li>• Layer 2 switch ports and VLAN trunks</li> <li>• IEEE 802.1Q VLAN encapsulation</li> <li>• Support for up to 4096 VLANs</li> <li>• Rapid Per-VLAN Spanning Tree Plus (PVRST+) (IEEE 802.1w compatible)</li> <li>• MSTP (IEEE 802.1s): 64 instances</li> <li>• Spanning Tree PortFast</li> <li>• Spanning Tree Root Guard</li> <li>• Spanning Tree Bridge Assurance</li> <li>• Cisco EtherChannel technology (up to 16 ports per EtherChannel)</li> <li>• LACP: IEEE 802.3ad</li> <li>• vPC</li> <li>• Advanced PortChannel hashing based on Layer 2, 3, and 4 information</li> <li>• Jumbo frames on all ports (up to 9216 bytes)</li> <li>• Storm control (unicast, multicast, and broadcast)</li> <li>• Private VLANs</li> </ul>

Description	Specification
<b>Layer 3</b>	<ul style="list-style-type: none"> <li>• Layer 3 interfaces: Routed ports on interfaces, switch virtual interfaces (SVIs), PortChannels, and subinterfaces (total: 1024)</li> <li>• 64-way Equal-Cost Multipath (ECMP)</li> <li>• 2000 ingress and 1000 egress ACL entries</li> <li>• Routing protocols: Static, RIPv2, EIGRP, OSPFv2, and BGP</li> <li>• Bidirectional Flow Detection (BFD) for BGP</li> <li>• HSRP and VRRP</li> <li>• ACL: Routed ACL with Layer 3 and 4 options to match ingress and egress ACLs</li> <li>• VRF: VRF-lite (IP VPN), VRF-aware unicast (BGP, OSPF, and RIP), and VRF-aware multicast</li> <li>• uRPF with ACL; strict and loose modes</li> <li>• Jumbo frame support (up to 9216 bytes)</li> </ul>
<b>Multicast</b>	<p>Multicast: PIM Version 2 Sparse Mode (PIM-SM) and SSM</p> <p>Bootstrap router (BSR), Automatic Rendezvous Point (Auto-RP) and Static RP</p> <p>Multicast Source Discovery Protocol (MSDP) and Anycast RP</p> <p>Internet Group Management Protocol (IGMP) Versions 2, and 3</p>
<b>Quality of service (QoS)</b>	<p>Layer 2 IEEE 802.1p (class of service [CoS])</p> <p>8 unicast and 4 multicast hardware queues per port</p> <p>Per-port QoS configuration</p> <p>CoS trust</p> <p>Port-based CoS assignment</p> <p>Modular QoS CLI (MQC) compliance</p> <p>ACL-based QoS classification (Layers 2, 3, and 4)</p> <p>MQC CoS marking</p> <p>Differentiated services code point (DSCP) marking</p> <p>Weighted Random Early Detection (WRED)</p> <p>CoS-based egress queuing</p> <p>Egress strict-priority queuing</p> <p>Egress port-based scheduling: Weighted Round-Robin (WRR)</p> <p>Explicit Congestion Notification (ECN)</p>
<b>Security</b>	<ul style="list-style-type: none"> <li>• Ingress ACLs (standard and extended) on Ethernet</li> <li>• Standard and extended Layer 3 to 4 ACLs: IPv4, Internet Control Message Protocol (ICMP), TCP, User Datagram Protocol (UDP), etc.</li> <li>• VLAN-based ACLs (VACLs)</li> <li>• Port-based ACLs (PACLs)</li> <li>• Named ACLs</li> <li>• ACLs on virtual terminals (vty)</li> <li>• DHCP snooping with Option 82</li> <li>• Port number in DHCP Option82</li> <li>• DHCP relay</li> <li>• Dynamic Address Resolution Protocol (ARP) inspection</li> <li>• Configurable CoPP</li> </ul>
<b>Cisco Nexus Data Broker</b>	<ul style="list-style-type: none"> <li>• Topology support for tap and SPAN aggregation</li> <li>• Support for QinQ to tag input source tap and SPAN ports</li> <li>• Traffic load balancing to multiple monitoring tools</li> <li>• Traffic filtering based on Layer 1 through Layer 4 header information</li> <li>• Traffic replication and forwarding to multiple monitoring tools</li> <li>• Robust RBAC</li> <li>• Northbound Representational State Transfer (REST) API for all programmability support</li> </ul>
<b>Management</b>	<ul style="list-style-type: none"> <li>• Switch management using 10/100/1000-Mbps management or console ports</li> <li>• CLI-based console to provide detailed out-of-band management</li> <li>• In-band switch management</li> <li>• Locator and beacon LEDs</li> <li>• Port-based locator and beacon LEDs</li> <li>• Configurable CoPP</li> <li>• Configuration rollback</li> </ul>

Description	Specification
	<ul style="list-style-type: none"> <li>• SSHv2</li> <li>• Telnet</li> <li>• AAA</li> <li>• AAA with RBAC</li> <li>• RADIUS</li> <li>• TACACS+</li> <li>• Syslog</li> <li>• Syslog generation on system resources (for example, FIB tables)</li> <li>• Embedded packet analyzer</li> <li>• SNMP v1, v2, and v3</li> <li>• Enhanced SNMP MIB support</li> <li>• XML (NETCONF) support</li> <li>• Remote monitoring (RMON)</li> <li>• Advanced Encryption Standard (AES) for management traffic</li> <li>• Unified username and passwords across CLI and SNMP</li> <li>• Microsoft Challenge Handshake Authentication Protocol (MS-CHAP)</li> <li>• Digital certificates for management between switch and RADIUS server</li> <li>• Cisco Discovery Protocol Versions 1 and 2</li> <li>• RBAC</li> <li>• Cisco SPAN on physical, PortChannel, VLAN, and Fibre Channel interfaces</li> <li>• ERSPAN</li> <li>• Ingress and egress packet counters per interface</li> <li>• PTP (IEEE 1588) boundary clock</li> <li>• Network Time Protocol (NTP)</li> <li>• Cisco OHMS</li> <li>• Comprehensive bootup diagnostic tests</li> <li>• Cisco Call Home</li> <li>• Cisco DCNM</li> <li>• Advanced buffer monitoring</li> </ul>

**Table 6.** Management and Standards Support

Description	Specification		
<b>MIB support</b>	<table border="0"> <tr> <td style="vertical-align: top;"> <p>Generic MIBs</p> <ul style="list-style-type: none"> <li>• SNMPv2-SMI</li> <li>• CISCO-SMI</li> <li>• SNMPv2-TM</li> <li>• SNMPv2-TC</li> <li>• IANA-ADDRESS-FAMILY-NUMBERS-MIB</li> <li>• IANAifType-MIB</li> <li>• IANAiprouteprotocol-MIB</li> <li>• HCNM-TC</li> <li>• CISCO-TC</li> <li>• SNMPv2-MIB</li> <li>• SNMP-COMMUNITY-MIB</li> <li>• SNMP-FRAMEWORK-MIB</li> <li>• SNMP-NOTIFICATION-MIB</li> <li>• SNMP-TARGET-MIB</li> <li>• SNMP-USER-BASED-SM-MIB</li> <li>• SNMP-VIEW-BASED-ACM-MIB</li> <li>• CISCO-SNMP-VACM-EXT-MIB</li> </ul> <p>Ethernet MIBs</p> <ul style="list-style-type: none"> <li>• CISCO-VLAN-MEMBERSHIP-MIB</li> <li>• LLDP-MIB</li> <li>• IP-MULTICAST-MIB</li> </ul> <p>Configuration MIBs</p> </td> <td style="vertical-align: top;"> <p>Monitoring MIBs</p> <ul style="list-style-type: none"> <li>• NOTIFICATION-LOG-MIB</li> <li>• CISCO-SYSLOG-EXT-MIB</li> <li>• CISCO-PROCESS-MIB</li> <li>• RMON-MIB</li> <li>• CISCO-RMON-CONFIG-MIB</li> <li>• CISCO-HC-ALARM-MIB</li> </ul> <p>Security MIBs</p> <ul style="list-style-type: none"> <li>• CISCO-AAA-SERVER-MIB</li> <li>• CISCO-AAA-SERVER-EXT-MIB</li> <li>• CISCO-COMMON-ROLES-MIB</li> <li>• CISCO-COMMON-MGMT-MIB</li> <li>• CISCO-SECURE-SHELL-MIB</li> </ul> <p>Miscellaneous MIBs</p> <ul style="list-style-type: none"> <li>• CISCO-LICENSE-MGR-MIB</li> <li>• CISCO-FEATURE-CONTROL-MIB</li> <li>• CISCO-CDP-MIB</li> <li>• CISCO-RF-MIB</li> </ul> <p>Layer 3 and Routing MIBs</p> <ul style="list-style-type: none"> <li>• UDP-MIB</li> <li>• TCP-MIB</li> <li>• OSPF-MIB</li> <li>• BGP4-MIB</li> </ul> </td> </tr> </table>	<p>Generic MIBs</p> <ul style="list-style-type: none"> <li>• SNMPv2-SMI</li> <li>• CISCO-SMI</li> <li>• SNMPv2-TM</li> <li>• SNMPv2-TC</li> <li>• IANA-ADDRESS-FAMILY-NUMBERS-MIB</li> <li>• IANAifType-MIB</li> <li>• IANAiprouteprotocol-MIB</li> <li>• HCNM-TC</li> <li>• CISCO-TC</li> <li>• SNMPv2-MIB</li> <li>• SNMP-COMMUNITY-MIB</li> <li>• SNMP-FRAMEWORK-MIB</li> <li>• SNMP-NOTIFICATION-MIB</li> <li>• SNMP-TARGET-MIB</li> <li>• SNMP-USER-BASED-SM-MIB</li> <li>• SNMP-VIEW-BASED-ACM-MIB</li> <li>• CISCO-SNMP-VACM-EXT-MIB</li> </ul> <p>Ethernet MIBs</p> <ul style="list-style-type: none"> <li>• CISCO-VLAN-MEMBERSHIP-MIB</li> <li>• LLDP-MIB</li> <li>• IP-MULTICAST-MIB</li> </ul> <p>Configuration MIBs</p>	<p>Monitoring MIBs</p> <ul style="list-style-type: none"> <li>• NOTIFICATION-LOG-MIB</li> <li>• CISCO-SYSLOG-EXT-MIB</li> <li>• CISCO-PROCESS-MIB</li> <li>• RMON-MIB</li> <li>• CISCO-RMON-CONFIG-MIB</li> <li>• CISCO-HC-ALARM-MIB</li> </ul> <p>Security MIBs</p> <ul style="list-style-type: none"> <li>• CISCO-AAA-SERVER-MIB</li> <li>• CISCO-AAA-SERVER-EXT-MIB</li> <li>• CISCO-COMMON-ROLES-MIB</li> <li>• CISCO-COMMON-MGMT-MIB</li> <li>• CISCO-SECURE-SHELL-MIB</li> </ul> <p>Miscellaneous MIBs</p> <ul style="list-style-type: none"> <li>• CISCO-LICENSE-MGR-MIB</li> <li>• CISCO-FEATURE-CONTROL-MIB</li> <li>• CISCO-CDP-MIB</li> <li>• CISCO-RF-MIB</li> </ul> <p>Layer 3 and Routing MIBs</p> <ul style="list-style-type: none"> <li>• UDP-MIB</li> <li>• TCP-MIB</li> <li>• OSPF-MIB</li> <li>• BGP4-MIB</li> </ul>
<p>Generic MIBs</p> <ul style="list-style-type: none"> <li>• SNMPv2-SMI</li> <li>• CISCO-SMI</li> <li>• SNMPv2-TM</li> <li>• SNMPv2-TC</li> <li>• IANA-ADDRESS-FAMILY-NUMBERS-MIB</li> <li>• IANAifType-MIB</li> <li>• IANAiprouteprotocol-MIB</li> <li>• HCNM-TC</li> <li>• CISCO-TC</li> <li>• SNMPv2-MIB</li> <li>• SNMP-COMMUNITY-MIB</li> <li>• SNMP-FRAMEWORK-MIB</li> <li>• SNMP-NOTIFICATION-MIB</li> <li>• SNMP-TARGET-MIB</li> <li>• SNMP-USER-BASED-SM-MIB</li> <li>• SNMP-VIEW-BASED-ACM-MIB</li> <li>• CISCO-SNMP-VACM-EXT-MIB</li> </ul> <p>Ethernet MIBs</p> <ul style="list-style-type: none"> <li>• CISCO-VLAN-MEMBERSHIP-MIB</li> <li>• LLDP-MIB</li> <li>• IP-MULTICAST-MIB</li> </ul> <p>Configuration MIBs</p>	<p>Monitoring MIBs</p> <ul style="list-style-type: none"> <li>• NOTIFICATION-LOG-MIB</li> <li>• CISCO-SYSLOG-EXT-MIB</li> <li>• CISCO-PROCESS-MIB</li> <li>• RMON-MIB</li> <li>• CISCO-RMON-CONFIG-MIB</li> <li>• CISCO-HC-ALARM-MIB</li> </ul> <p>Security MIBs</p> <ul style="list-style-type: none"> <li>• CISCO-AAA-SERVER-MIB</li> <li>• CISCO-AAA-SERVER-EXT-MIB</li> <li>• CISCO-COMMON-ROLES-MIB</li> <li>• CISCO-COMMON-MGMT-MIB</li> <li>• CISCO-SECURE-SHELL-MIB</li> </ul> <p>Miscellaneous MIBs</p> <ul style="list-style-type: none"> <li>• CISCO-LICENSE-MGR-MIB</li> <li>• CISCO-FEATURE-CONTROL-MIB</li> <li>• CISCO-CDP-MIB</li> <li>• CISCO-RF-MIB</li> </ul> <p>Layer 3 and Routing MIBs</p> <ul style="list-style-type: none"> <li>• UDP-MIB</li> <li>• TCP-MIB</li> <li>• OSPF-MIB</li> <li>• BGP4-MIB</li> </ul>		



Description	Specification	
	<ul style="list-style-type: none"> <li>• ENTITY-MIB</li> <li>• IF-MIB</li> <li>• CISCO-ENTITY-EXT-MIB</li> <li>• CISCO-ENTITY-FRU-CONTROL-MIB</li> <li>• CISCO-ENTITY-SENSOR-MIB</li> <li>• CISCO-SYSTEM-MIB</li> <li>• CISCO-SYSTEM-EXT-MIB</li> <li>• CISCO-IP-IF-MIB</li> <li>• CISCO-IF-EXTENSION-MIB</li> <li>• CISCO-NTP-MIB</li> <li>• CISCO-IMAGE-MIB</li> <li>• CISCO-IMAGE-UPGRADE-MIB</li> </ul>	<ul style="list-style-type: none"> <li>• CISCO-HSRP-MIB</li> </ul>
<b>Standards</b>	<ul style="list-style-type: none"> <li>• IEEE 802.1D: Spanning Tree Protocol</li> <li>• IEEE 802.1p: CoS Prioritization</li> <li>• IEEE 802.1Q: VLAN Tagging</li> <li>• IEEE 802.1s: Multiple VLAN Instances of Spanning Tree Protocol</li> <li>• IEEE 802.1w: Rapid Reconfiguration of Spanning Tree Protocol</li> <li>• IEEE 802.3z: Gigabit Ethernet</li> <li>• IEEE 802.3ad: Link Aggregation Control Protocol (LACP)</li> <li>• IEEE 802.3ae: 10 Gigabit Ethernet</li> <li>• IEEE 802.1ab: LLDP</li> <li>• IEEE 1588-2008: Precision Time Protocol (Boundary Clock)</li> </ul>	
<b>RFC</b>	<p data-bbox="542 974 592 1003"><b>BGP</b></p> <ul style="list-style-type: none"> <li>• RFC 1997: BGP Communities Attribute</li> <li>• RFC 2385: Protection of BGP Sessions with the TCP MD5 Signature Option</li> <li>• RFC 2439: BGP Route Flap Damping</li> <li>• RFC 2519: A Framework for Inter-Domain Route Aggregation</li> <li>• RFC 2545: Use of BGPv4 Multiprotocol Extensions</li> <li>• RFC 2858: Multiprotocol Extensions for BGPv4</li> <li>• RFC 3065: Autonomous System Confederations for BGP</li> <li>• RFC 3392: Capabilities Advertisement with BGPv4</li> <li>• RFC 4271: BGPv4</li> <li>• RFC 4273: BGPv4 MIB: Definitions of Managed Objects for BGPv4</li> <li>• RFC 4456: BGP Route Reflection</li> <li>• RFC 4486: Subcodes for BGP Cease Notification Message</li> <li>• RFC 4724: Graceful Restart Mechanism for BGP</li> <li>• RFC 4893: BGP Support for Four-Octet AS Number Space</li> </ul> <p data-bbox="542 1423 602 1453"><b>OSPF</b></p> <ul style="list-style-type: none"> <li>• RFC 2328: OSPF Version 2</li> <li>• 8431RFC 3101: OSPF Not-So-Stubby-Area (NSSA) Option</li> <li>• RFC 3137: OSPF Stub Router Advertisement</li> <li>• RFC 3509: Alternative Implementations of OSPF Area Border Routers</li> <li>• RFC 3623: Graceful OSPF Restart</li> <li>• RFC 4750: OSPF Version 2 MIB</li> </ul> <p data-bbox="542 1625 586 1654"><b>RIP</b></p> <ul style="list-style-type: none"> <li>• RFC 1724: RIPv2 MIB Extension</li> <li>• RFC 2082: RIPv2 MD5 Authentication</li> <li>• RFC 2453: RIP Version 2</li> <li>• IP Services</li> <li>• RFC 768: User Datagram Protocol (UDP)</li> <li>• RFC 783: Trivial File Transfer Protocol (TFTP)</li> <li>• RFC 791: IP</li> <li>• RFC 792: ICMP</li> <li>• RFC 793: TCP</li> <li>• RFC 826: ARP</li> </ul>	

Description	Specification
	<ul style="list-style-type: none"> <li>• RFC 854: Telnet</li> <li>• RFC 959: FTP</li> <li>• RFC 1027: Proxy ARP</li> <li>• RFC 1305: Network Time Protocol (NTP) Version 3</li> <li>• RFC 1519: Classless Interdomain Routing (CIDR)</li> <li>• RFC 1542: BootP Relay</li> <li>• RFC 1591: Domain Name System (DNS) Client</li> <li>• RFC 1812: IPv4 Routers</li> <li>• RFC 2131: DHCP Helper</li> <li>• RFC 2338: VRRP</li> </ul> <p>IP Multicast</p> <ul style="list-style-type: none"> <li>• RFC 2236: Internet Group Management Protocol, version 2</li> <li>• RFC 3376: Internet Group Management Protocol, Version 3</li> <li>• RFC 3446: Anycast Rendezvous Point Mechanism Using PIM and MSDP</li> <li>• RFC 3569: An Overview of SSM</li> <li>• RFC 3618: Multicast Source Discovery Protocol (MSDP)</li> <li>• RFC 4601: Protocol Independent Multicast - Sparse Mode (PIM-SM): Protocol Specification (Revised)</li> <li>• RFC 4607: Source-Specific Multicast for IP</li> <li>• RFC 4610: Anycast-RP using PIM</li> <li>• RFC 5132: IP Multicast MIB</li> </ul>

## Software Requirements

Cisco Nexus 3000 Series Switches are supported by Cisco NX-OS Software Release 5.0 and later. Cisco NX-OS interoperates with any networking OS, including Cisco IOS Software, that conforms to the networking standards mentioned in this data sheet.

## Regulatory Standards Compliance

Table 7 summarizes regulatory standards compliance for the Cisco Nexus 3000 Series.

**Table 7.** Regulatory Standards Compliance: Safety and EMC

Specification	Description
<b>Regulatory compliance</b>	<ul style="list-style-type: none"> <li>• Products should comply with CE Markings per directives 2004/108/EC and 2006/95/EC</li> </ul>
<b>Safety</b>	<ul style="list-style-type: none"> <li>• UL 60950-1 Second Edition</li> <li>• CAN/CSA-C22.2 No. 60950-1 Second Edition</li> <li>• EN 60950-1 Second Edition</li> <li>• IEC 60950-1 Second Edition</li> <li>• AS/NZS 60950-1</li> <li>• GB4943</li> </ul>
<b>EMC: Emissions</b>	<ul style="list-style-type: none"> <li>• 47CFR Part 15 (CFR 47) Class A</li> <li>• AS/NZS CISPR22 Class A</li> <li>• CISPR22 Class A</li> <li>• EN55022 Class A</li> <li>• ICES003 Class A</li> <li>• VCCI Class A</li> <li>• EN61000-3-2</li> <li>• EN61000-3-3</li> <li>• KN22 Class A</li> <li>• CNS13438 Class A</li> </ul>
<b>EMC: Immunity</b>	<ul style="list-style-type: none"> <li>• EN55024</li> <li>• CISPR24</li> <li>• EN300386</li> <li>• KN24</li> </ul>

## Ordering Information

Table 8 provides ordering information for the Cisco Nexus 3016.

**Table 8.** Ordering Information

Part Number	Description
<b>Chassis</b>	
<b>N3K-C3016Q-40GE</b>	Nexus 3016, 16 QSFP+ ports, 1RU switch
<b>N3K-C3064-FAN</b>	Nexus 3064 Fan Module, Forward airflow (port side exhaust)
<b>N3K-C3064-FAN-B</b>	Nexus 3064 Fan Module, Reversed airflow (port side intake)
<b>N2200-PAC-400W</b>	N2K/3K 400W AC Power Supply, Forward airflow (port side exhaust)
<b>N2200-PAC-400W-B</b>	N2K/3K 400W AC Power Supply, Reversed airflow (port side intake)
<b>N2200-PDC-400W</b>	N2K/3K 400W DC Power Supply, Forward airflow (port side exhaust)
<b>N3K-PDC-350W-B</b>	N3K Series 350W DC Power Supply, Reversed airflow (port side intake)
<b>Software Licenses</b>	
<b>N3K-BAS1K9</b>	Nexus 3000 Layer 3 Base License
<b>N3K-LAN1K9</b>	Nexus 3000 Layer 3 LAN Enterprise License (Requires N3K-BAS1K9 License)
<b>NDB-FX-SWT-K9</b>	License for Tap/SPAN aggregation using Cisco Nexus Data Broker
<b>Spares</b>	
<b>N3K-C3064-FAN=</b>	Nexus 3064 Fan Module, Forward airflow (port side exhaust), Spare
<b>N3K-C3064-FAN-B=</b>	Nexus 3064 Fan Module, Reversed airflow (port side intake), Spare
<b>N2000-PAC-400W=</b>	N2K/3K 400W AC Power Supply, Forward airflow (port side exhaust), Spare
<b>N2000-PAC-400W-B=</b>	N2K/3K 400W AC Power Supply, Reversed airflow (port side intake), Spare
<b>N2200-PDC-400W=</b>	N2K/3K 400W DC Power Supply, Forward airflow (port side exhaust), Spare
<b>N3K-PDC-350W-B=</b>	N3K Series 350W DC Power Supply, Reversed airflow (port side intake), Spare
<b>N3K-C3064-ACC-KIT=</b>	Nexus 3064PQ Accessory Kit
<b>Bundles</b>	
<b>N3K-C3016-FA-L3</b>	Nexus 3016, AC, Forward Airflow (port side exhaust), Base & LAN Ent Lic Bundle
<b>N3K-C3016-BA-L3</b>	Nexus 3016, AC, Reversed Airflow (port side intake), Base & LAN Ent Lic Bundle
<b>N3K-C3016-FD-L3</b>	Nexus 3016, DC, Forward Airflow (port side exhaust), Base & LAN Ent Lic Bundle
<b>N3K-C3016-BD-L3</b>	Nexus 3016, DC, Reversed Airflow (port side intake), Base & LAN Ent Lic Bundle
<b>Cables and Optics</b>	
<b>QSFP-40G-SR4</b>	40GBASE-SR4 QSFP Transceiver Module with MPO Connector
<b>QSFP-H40G-CU1M</b>	40GBASE-CR4 Passive Copper Cable, 1m
<b>QSFP-H40G-CU3M</b>	40GBASE-CR4 Passive Copper Cable, 3m
<b>QSFP-H40G-CU5M</b>	40GBASE-CR4 Passive Copper Cable, 5m
<b>QSFP-4SFP10G-CU1M</b>	QSFP to 4xSFP10G Passive Copper Splitter Cable, 1m
<b>QSFP-4SFP10G-CU3M</b>	QSFP to 4xSFP10G Passive Copper Splitter Cable, 3m
<b>QSFP-4SFP10G-CU5M</b>	QSFP to 4xSFP10G Passive Copper Splitter Cable, 5m

---

## Service and Support

Cisco offers a wide range of services to help accelerate your success in deploying and optimizing the Cisco Nexus 3000 Series in your data center. The innovative Cisco Services offerings are delivered through a unique combination of people, processes, tools, and partners and are focused on helping you increase operation efficiency and improve your data center network. Cisco Advanced Services uses an architecture-led approach to help you align your data center infrastructure with your business goals and achieve long-term value. Cisco SMARTnet<sup>®</sup> Service helps you resolve mission-critical problems with direct access at any time to Cisco network experts and award-winning resources. With this service, you can take advantage of the Cisco Smart Call Home service capability, which offers proactive diagnostics and real-time alerts on your Cisco Nexus 3000 Series Switches. Spanning the entire network lifecycle, Cisco Services helps increase investment protection, optimize network operations, support migration operations, and strengthen your IT expertise.

## Cisco Capital Financing to Help You Achieve Your Objectives

Cisco Capital<sup>®</sup> financing can help you acquire the technology you need to achieve your objectives and stay competitive. We can help you reduce capital expenditures (CapEx), accelerate your growth, and optimize your investment dollars and ROI. Cisco Capital financing gives you flexibility in acquiring hardware, software, services, and complementary third-party equipment. And you have just one predictable payment. Cisco Capital financing is available in more than 100 countries. [Learn more.](#)

## For More Information

For more information, please visit <http://www.cisco.com/go/nexus3000>. For information about Cisco Nexus Data Broker, please visit <http://www.cisco.com/go/nexusdatabroker>.



---

Americas Headquarters  
Cisco Systems, Inc.  
San Jose, CA

Asia Pacific Headquarters  
Cisco Systems (USA) Pte. Ltd.  
Singapore

Europe Headquarters  
Cisco Systems International BV Amsterdam,  
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: [www.cisco.com/go/trademarks](http://www.cisco.com/go/trademarks). Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)