



Cisco UCS B230 M2 Blade Server

CISCO SYSTEMS
170 WEST TASMAN DR.
SAN JOSE, CA, 95134
WWW.CISCO.COM

PUBLICATION HISTORY

REV A.8 MARCH 4, 2013

OVERVIEW	3
DETAILED VIEWS	4
Chassis Front View	4
BASE SERVER STANDARD CAPABILITIES and FEATURES	5
CONFIGURING the SERVER	6
STEP 1 VERIFY BASE SKU	7
STEP 2 CHOOSE CPU(S)	8
STEP 3 CHOOSE MEMORY	9
STEP 4 CHOOSE SOLID STATE DRIVES	13
STEP 5 CHOOSE MEZZANINE OPTION CARD	14
STEP 6 CHOOSE OPERATING SYSTEM	15
STEP 7 CHOOSE OPERATING SYSTEM MEDIA KIT	17
STEP 8 CHOOSE OPTIONAL VALUE-ADDED SOFTWARE	18
STEP 9 CHOOSE SERVICE and SUPPORT LEVEL	19
ORDER OPTIONAL KVM CABLE	24
SUPPLEMENTAL MATERIAL	25
Motherboard	25
DIMM and CPU Layout	26
Memory Population Recommendations	27
TECHNICAL SPECIFICATIONS	29
Dimensions and Weight	29
Power Specifications	29

OVERVIEW

The Cisco® UCS B230 M2 Blade Server is a two-socket, half-width blade server that extends the capabilities of the Cisco Unified Computing System™, using Intel's Xeon E7-2800 and E7-8800 Series multi-core processors with 32 DIMM slots, one mezzanine slot, and up to two solid-state drives (SSDs). Up to eight half-width blade servers can be accommodated in the Cisco UCS 5108 Blade Server Chassis. The UCS B230 M2 server is shown in [Figure 1](#).

Figure 1 Cisco UCS B230 M2 Blade Server




DETAILED VIEWS

Chassis Front View

Figure 2 shows the front of the Cisco UCS B230 M2 Blade Server.

Figure 2 Chassis Front View



1	SSD 1 activity LED	9	Beaoning LED and button
2	SSD 1 Fault/Locate LED	10	System activity LED
3	SSD sled in bay 1	11	Blade health LED
4	SSD 2 activity LED	12	Reset button access
5	SSD 2 fault LED	13	Power button and LED
6	Ejector lever captive screw	14	Console connector ¹
7	Ejector lever	15	Asset tab ²
8	SSD sled in bay 2	-	-

Notes . . .

1. For more information regarding the KVM cable connection, see [ORDER OPTIONAL KVM CABLE on page 24](#)
2. Each server has a blank plastic tag that pulls out of the front panel, provided so you can add your own asset tracking label without interfering with the intended air flow

BASE SERVER STANDARD CAPABILITIES and FEATURES

Table 1 lists the capabilities and features of the base server. Details about how to configure the server for a particular feature or capability (for example, number of processors, disk drives, or amount of memory) are provided in [CONFIGURING the SERVER on page 6](#).

Table 1 Capabilities and Features

Capability/Feature	Description
Chassis	The B230 M2 Blade Server mounts in a Cisco UCS 5100-series chassis
CPU	Either 1 or 2 Intel® Xeon® E7-2800 or E7-8800 series processors
Chipset	Intel® 7510 chipset
Memory	32 slots for registered DIMMs, up to 512 GB.
Expansion slots	One mezzanine slot is provided
Storage controller	LSI SAS 2008 RAID controller (onboard version of LSI MegaRAID 9240)
Internal storage devices	Up to two optional front-accessible, hot-swappable low-height 7 mm form factor SATA solid-state disk drives (SSDs).
Video	The server CIMC chip includes a Matrox G200 core. The first 8 MB of memory are allocated to the video core.
Interfaces	One front-accessible console connector (see ORDER OPTIONAL KVM CABLE on page 24)
Power subsystem	Integrated in the Cisco UCS 5100 series chassis
Fans	Integrated in the Cisco UCS 5100 series chassis
Integrated management processor	The built-in Cisco Integrated Management Controller (CIMC) GUI or CLI interface enables you to monitor the server inventory, health, and system event logs.

CONFIGURING the SERVER

Follow these steps to configure the Cisco UCS B230 M2 Server:

- [STEP 1 VERIFY BASE SKU, page 7](#)
- [STEP 2 CHOOSE CPU\(S\), page 8](#)
- [STEP 3 CHOOSE MEMORY, page 9](#)
- [STEP 4 CHOOSE SOLID STATE DRIVES, page 13](#)
- [STEP 5 CHOOSE MEZZANINE OPTION CARD, page 14](#)
- [STEP 6 CHOOSE OPERATING SYSTEM, page 15](#)
- [STEP 7 CHOOSE OPERATING SYSTEM MEDIA KIT, page 17](#)
- [STEP 8 CHOOSE OPTIONAL VALUE-ADDED SOFTWARE, page 18](#)
- [STEP 9 CHOOSE SERVICE and SUPPORT LEVEL, page 19](#)

STEP 1 VERIFY BASE SKU

Verify the product ID (PID) of the base server as shown in [Table 2](#).

Table 2 PID of the Base B230 M2 Server

Product ID (PID)	Description
B230-BASE-M2	UCS B230 M2 Blade Server w/o CPU, memory, SSD, mezzanine

The B230-BASE-M2 base server:

- Does not include CPUs, memory DIMMs, solid-state Drives (SSDs), or a mezzanine card.



NOTE: Use the steps on the following pages to configure the server with the components that you want to include.

STEP 2 CHOOSE CPU(S)

The standard CPU features are:

- Intel Xeon E7-2800 or E7-8800 series CPUs
- Intel 7510 chipset
- Cache size of 18, 24, or 30 MB

Choose CPUs

The available CPUs are listed in [Table 3](#).

Table 3 Available CPUs: Intel Xeon E7-28xx/8867L Family

Product ID (PID)	Intel Number	Clock Freq (GHz)	Power (W)	Cache Size (MB)	Cores	QPI	Highest DDR3 DIMM Clock Support (MHz)
UCS-CPU-E78867L	E7-8867L	2.13	105	30	10	6.40	1333 ¹
UCS-CPU-E72870	E7-2870	2.40	130	30	10	6.40	1333 ¹
UCS-CPU-E72860	E7-2860	2.26	130	24	10	6.40	1333 ¹
UCS-CPU-E72850	E7-2850	2.00	130	24	10	6.40	1333 ¹
UCS-CPU-E27830	E7-2830	2.13	105	24	8	6.40	1333 ¹
UCS-CPU-E72803	E7-2803	1.73	105	18	6	4.80	1333 ²

Notes . . .

1. Maximum operational speed = 1066 MHz
2. Maximum operational speed = 800 MHz

Approved Configurations

(1) One-CPU Configuration

- Choose one CPU from [Table 3](#).

(2) Two-CPU Configuration

- Choose two CPUs from any one row of [Table 3](#).

Caveats

- You must choose one processor or two identical processors.

STEP 3 CHOOSE MEMORY

The standard memory features are:

- DIMMs
 - Maximum memory bandwidth: 800 MHz for E7-2803, 1066 MHz for all other CPUs
 - Ranks per DIMM: 1, 2, or 4
 - Operational voltage: 1.35 V
 - Registered DIMMs (RDIMMs)
 - Mirroring option
 - Advanced error correcting code (ECC)
 - Double device data correction (DDDC)




NOTE: DDDC support applies to x4 DIMMs only.

- Each CPU controls four DDR3 channels. Each of the channels controls four DIMMs. The maximum number of DIMMs that can be installed per CPU is 16 (8 DIMM kits). See [Figure 3](#).



NOTE: Memory mirroring is supported and settable using the UCSM Service Profile “Memory RAS Configuration” setting.

Figure 3 B230 M2 Memory Organization



Select DIMMs

DIMMs are available as two-DIMM kits. Each of the product IDs in [Table 4](#) specifies two DIMMs.

Table 4 Available DDR3 DIMMs

Product ID (PID)	PID Description	Voltage	Ranks/ DIMM
DIMM Pair Kit Options (2 DIMMs per kit)			
UCS-MR-2X041RX-C	2x4GB DDR3-1333-MHz RDIMM/PC3-10600/1R/x8/1.35v	1.5/1.35 V	1
UCS-MR-2X082RX-C	2x8GB DDR3-1333-MHz RDIMM/PC3-10600/2R/x4/1.35v	1.5/1.35 V	2
UCS-MR-2X164RX-D	2x16GB NHS DDR3-1333-MHz RDIMM/PC3-10600/4R/x4/1.35v	1.5/1.35 V	4

Approved Configurations

(1) 1-CPU Configuration

- 16 DIMMs capacity total
- Select from one to eight DIMM kits (two to 16 DIMMs) per CPU. The DIMMs will be placed by the factory as shown in the following table:

Number of DIMMs	DIMM Placement in Numbered/Colored DIMM Slots (see Figure 7 on page 27)
2	(B0, B1) - blue slots
4	(B0, B1) - (D0, D1) - blue slots
6	(B0, B1) - (D0, D1) - blue slots; (A0, A1) - white slots
8	(B0, B1) - (D0, D1) - blue slots; (A0, A1) - (C0, C1) - white slots
10	(B0, B1) - (D0, D1) - blue slots; (A0, A1) - (C0, C1) - white slots; (B2, B3) - yellow slots
12	(B0, B1) - (D0, D1) - blue slots; (A0, A1) - (C0, C1) - white slots (B2, B3) - (D2, D3) - yellow slots
14	(B0, B1) - (D0, D1) - blue slots; (A0, A1) - (C0, C1) - white slots (B2, B3) - (D2, D3) - yellow slots; (A2, A3) - black slots
16	(B0, B1) - (D0, D1) - blue slots; (A0, A1) - (C0, C1) - white slots (B2, B3) - (D2, D3) - yellow slots; (A2, A3) - (C2, C3) - black slots

(2) 2-CPU Configuration

- 32 DIMMs capacity total
- Select from one to eight DIMM kits (two to 16 DIMMs) per CPU. The DIMMs will be placed by the factory as shown in the following table:

Number of DIMMs per CPU	DIMM Placement in Numbered/Colored DIMM Slots (see Figure 7 on page 27)
2	CPU 1: (B0, B1) - blue slots CPU 2: (B0, B1) - blue slots
4	CPU 1: (B0, B1) - (D0, D1) - blue slots CPU 2: (B0, B1) - (D0, D1) - blue slots
6	CPU 1: (B0, B1) - (D0, D1) - blue slots; (A0, A1) - white slots CPU 2: (B0, B1) - (D0, D1) - blue slots; (A0, A1) - white slots
8	CPU 1: (B0, B1) - (D0, D1) - blue slots; (A0, A1) - (C0, C1) - white slots CPU 2: (B0, B1) - (D0, D1) - blue slots; (A0, A1) - (C0, C1) - white slots

10	CPU 1: (B0, B1) - (D0, D1) - blue slots; (A0, A1) - (C0, C1) - white slots; (B2, B3) - yellow slots CPU 2: (B0, B1) - (D0, D1) - blue slots; (A0, A1) - (C0, C1) - white slots; (B2, B3) - yellow slots
12	CPU 1: (B0, B1) - (D0, D1) - blue slots; (A0, A1) - (C0, C1) - white slots (B2, B3) - (D2, D3) - yellow slots CPU 2: (B0, B1) - (D0, D1) - blue slots; (A0, A1) - (C0, C1) - white slots (B2, B3) - (D2, D3) - yellow slots
14	CPU 1: (B0, B1) - (D0, D1) - blue slots; (A0, A1) - (C0, C1) - white slots (B2, B3) - (D2, D3) - yellow slots; (A2, A3) - black slots CPU 2: (B0, B1) - (D0, D1) - blue slots; (A0, A1) - (C0, C1) - white slots (B2, B3) - (D2, D3) - yellow slots; (A2, A3) - black slots
16	CPU 1: (B0, B1) - (D0, D1) - blue slots; (A0, A1) - (C0, C1) - white slots (B2, B3) - (D2, D3) - yellow slots; (A2, A3) - (C2, C3) - black slots CPU 2: (B0, B1) - (D0, D1) - blue slots; (A0, A1) - (C0, C1) - white slots (B2, B3) - (D2, D3) - yellow slots; (A2, A3) - (C2, C3) - black slots

Caveats

- The B230 M2 server needs at least one DIMM pair installed for each CPU.
- One DIMM pair on a CPU can be different from other pairs; however, DIMMs sold as kits are matched pairs and must remain together when installed in a particular pair of same-colored (blue, white, yellow, or black) pairs of slots.
- The DIMMs installed in slots for an absent CPU are not recognized.
- Memory DIMMs should be installed evenly across the installed CPUs. Though this is not a requirement, if not done it results in performance degradation. The preferred DIMM installations are highlighted in green in the tables.

STEP 4 CHOOSE SOLID STATE DRIVES

The standard disk drive features are:

- 7 mm low-height form factor solid state drives
- Hot-pluggable
- Sled-mounted

Choose Drives

The available drives are listed in [Table 5](#).

Table 5 Available Hot-Pluggable Sled-Mounted SSDs

Product ID (PID)	PID Description	Drive Type	Capacity
UCS-SD300G0KA2-T	300 GB Low-Height 8mm SATA SSD	SATA	300 GB
UCS-SD200G0KA2-T	200 GB Low-Height 8mm SATA SSD	SATA	200 GB
UCS-SSD100GI1F105	100 GB Low-Height 7mm SATA SSD	SATA	100 GB

Approved Configurations

(1) 1-Drive Configuration

- Select one drive from [Table 5](#).

(2) 2-Drive Configuration

- Select two drives from [Table 5](#).

Caveats

- None

STEP 5 CHOOSE MEZZANINE OPTION CARD

The standard PCIe card offerings are:

- Converged Network Adapters (CNA)
- Network Interface Cards (NICs)

Choose a PCIe Option Card

The available PCIe option cards are listed in [Table 6](#).

Table 6 Available PCIe Option Cards

Product ID (PID)	PID Description
Converged Network Adapters (CNA)	
N20-AQ0102	Cisco UCS CNA M72KR-Q Qlogic Adapter
N20-AE0102	Cisco UCS CNA M72KR-E Emulex Adapter
N20-AI0102	Cisco UCS CNA M61KR-I Intel Converged Network Adapter
UCS-VIC-M82-8P	Cisco UCS VIC 1280 dual 40Gb capable Virtual Interface Card
Network Interface Cards (NICs)	
N20-AB0002	Cisco UCS M51KR-B Broadcom 57711 Adapter

Approved Configurations

(1) Select one PCIe Mezzanine Card (mandatory)

You must select one card.

To help ensure that your operating system is compatible with the card you have selected, please check the Hardware Compatibility List at this URL:

http://www.cisco.com/en/US/products/ps10477/prod_technical_reference_list.html

STEP 6 CHOOSE OPERATING SYSTEM

Several operating systems are available from which to choose. Choose one of the operating systems listed in [Table 7](#).

Table 7 Operating Systems

PID Description	Product ID (PID)
Red Hat Enterprise Linux	
RHEL-2S-1G-1A	RHEL/2 Socket/1 Guest/1Yr Svcs Required
RHEL-2S-1G-3A	RHEL/2 Socket/1 Guest/3Yr Svcs Required
RHEL-2S-4G-1A	RHEL/2 Socket/4 Guest/1Yr Svcs Required
RHEL-2S-4G-3A	RHEL/2 Socket/4 Guest/3Yr Svcs Required
RHEL-2S-UG-1A	RHEL/2 Socket/U Guest/1Yr Svcs Required
RHEL-2S-UG-3A	RHEL/2 Socket/U Guest/3Yr Svcs Required
RHEL-2S-1G-1A-RS	RHEL/2 Socket/1 Guest/1Yr Subscription/Redhat Svcs Included
RHEL-2S-1G-3A-RS	RHEL/2 Socket/1 Guest/3Yr Subscription/Redhat Svcs Included
RHEL-2S-4G-3A-RS	RHEL/2 Socket/2 Guest/3Yr Subscription/Redhat Svcs Included
RHEL-2S-4G-1A-RS	RHEL/2 Socket/4 Guest/1Yr Subscription/Redhat Svcs Included
RHEL-2S-UG-1A-RS	RHEL/2 Socket/U Guest/1Yr Subscription/Redhat Svcs Included
RHEL-2S-UG-3A-RS	RHEL/2 Socket/U Guest/3Yr Subscription/Redhat Svcs Included
RHEL Add-Ons	
RHEL-HA-2S-1A	RHEL Option/High-Availability/2 Socket/1Yr Svcs Required
RHEL-RS-2S-1A	RHEL Option/Resilient w/Ha /2 Socket/1 Yr Svcs Required
RHEL-SFS-2S-1A	RHEL Option/Scalable File System/2 Socket/1 Yr Svcs Required
RHEL-HA-2S-3A	RHEL Option/High-Availability/2 Socket/3Yr Svcs Required
RHEL-RS-2S-3A	RHEL Option/Resilient Storage w/ HA /2 Socket/3 Yr Svcs Req'd
RHEL-SFS-2S-3A	RHEL Option/Scalable File System/2 Socket/3 Yr Svcs Required
RHEL-HA-2S-1A-RS	RHEL Option/High-Availability/2 Socket/1Yr Redhat Svcs Incl'd
RHEL-RS-2S-1A-RS	RHEL Option/Resilient Storage/2 Socket/1 Yr Redhat Svcs Incl
RHEL-SFS-2S-1A-RS	RHEL Option/Scalable File Sys/2 Socket/1 Yr Redhat Svcs Incl
RHEL-HA-2S-3A-RS	RHEL Option/High-Availability/2 Socket/3Yr Redhat Svcs Incl'd
RHEL-RS-2S-3A-RS	RHEL Option/Resilient Storage/2 Socket/3 Yr Redhat Svcs Incl
RHEL-SFS-2S-3A-RS	RHEL Option/Scalable File Sys/2 Socket/3 Yr Redhat Svcs Incl
Windows Server	
MSWS-08R2-STHV	Windows Svr 2008 ST media R2 ST (1-4CPU, 5CAL)
MSWS-08R2-ENHV	Windows Svr 2008 EN media R2 EN (1-8CPU, 25CAL)
MSWS-08R2-DCHV2S	Windows Svr 2008 R2-2 CPU-Data Center

Table 7 Operating Systems (continued)

PID Description	Product ID (PID)
MSWS-08R2-DCHV4S	Windows Svr 2008 R2-4 CPU-Data Center
VMWare Server	
VMW-VS5-STD-1A	VMware vSphere 5 Standard for 1 Processor, 1 Year, Support Req
VMW-VS5-STD-2A	VMware vSphere 5 Standard for 1 Processor, 2 Year, Support Req
VMW-VS5-STD-3A	VMware vSphere 5 Standard for 1 Processor, 3 Year, Support Req
VMW-VS5-STD-4A	VMware vSphere 5 Standard for 1 Processor, 4 Year, Support Req
VMW-VS5-STD-5A	VMware vSphere 5 Standard for 1 Processor, 5 Year, Support Req
VMW-VS5-ENT-1A	VMware vSphere 5 Enterprise for 1 Processor, 1 Year Support Req
VMW-VS5-ENT-2A	VMware vSphere 5 Enterprise for 1 Processor, 2 Year Support Req
VMW-VS5-ENT-3A	VMware vSphere 5 Enterprise for 1 Processor, 3 Year Support Req
VMW-VS5-ENT-4A	VMware vSphere 5 Enterprise for 1 Processor, 4 Year Support Req
VMW-VS5-ENT-5A	VMware vSphere 5 Enterprise for 1 Processor, 5 Year Support Req
VMW-VS5-ENTP-1A	VMware vSphere 5 Enterprise Plus for 1 Processor, 1 Year, Supp Req
VMW-VS5-ENTP-2A	VMware vSphere 5 Enterprise Plus for 1 Processor, 2 Year, Supp Req
VMW-VS5-ENTP-3A	VMware vSphere 5 Enterprise Plus for 1 Processor, 3 Year, Supp Req
VMW-VS5-ENTP-4A	VMware vSphere 5 Enterprise Plus for 1 Processor, 4 Year, Supp Req
VMW-VS5-ENTP-5A	VMware vSphere 5 Enterprise Plus for 1 Processor, 5 Year, Supp Req
VMW-VC5-ST-1A	VMware vCenter 5 Standard for 1 Processor, 1 Year, Support Required
VMW-VC5-ST-2A	VMware vCenter 5 Standard for 1 Processor, 2 Year, Support Required
VMW-VC5-ST-3A	VMware vCenter 5 Standard for 1 Processor, 3 Year, Support Required
VMW-VC5-ST-4A	VMware vCenter 5 Standard for 1 Processor, 4 Year, Support Required
VMW-VC5-ST-5A	VMware vCenter 5 Standard for 1 Processor, 5 Year, Support Required
Novell	
SLES-1A	SLES/1yr subscription/Svcs Required/0 media
SLES-3A	SLES/3yr subscription/Svcs Required/0 media

STEP 7 CHOOSE OPERATING SYSTEM MEDIA KIT

Choose the optional operating system media listed in [Table 8](#).

Table 8 OS Media

Product ID (PID)	PID Description
RHEL-6	RHEL 6 Recovery Media Only (Multilingual)
SLES-11	SLES 11 media only (multilingual)
MSWS-08R2-STHV-RM	Windows Svr 2008 R2 ST (1-4CPU, 5CAL), Media
MSWS-08RS-ENHV-RM	Windows Svr 2008 R2 EN (1-8CPU, 25CAL), Media
MSWS-08R2-DCHV-RM	Windows Svr 2008 R2 DC (1-8CPU, 25CAL), Media

STEP 8 CHOOSE OPTIONAL VALUE-ADDED SOFTWARE

You can select from a variety of value-added software listed in [Table 9](#).

Table 9 Value-Added Software

Product ID (PID)	PID Description
BMC-012	BMC BPPM Per Server
BMC-SE-4C	BMC BladeLogic Standard Edition, 4 Cores, Support Required
BMC-SE-6C	BMC BladeLogic Standard Edition, 6 Cores, Support Required
BMC-SE-8C	BMC BladeLogic Standard Edition, 8 Cores, Support Required
BMC-SE-10C	BMC BladeLogic Standard Edition, 10 Cores, Support Required
BMC-AE-4C	BMC BladeLogic Advanced Edition, 4 Cores, Support Required
BMC-AE-6C	BMC BladeLogic Advanced Edition, 6 Cores, Support Required
BMC-AE-8C	BMC BladeLogic Advanced Edition, 8 Cores, Support Required
BMC-AE-10C	BMC BladeLogic Advanced Edition, 10 Cores, Support Required
N1K-CSK9-UCS-404	Cisco Nexus 1000V VSM Virtual Appliance Software

STEP 9 CHOOSE SERVICE and SUPPORT LEVEL

A variety of service options are available, as described in this section.

Unified Computing Warranty, No Contract

If you have noncritical implementations and choose to have no service contract, the following coverage is supplied:

- Three-year parts coverage.
- Next business day (NBD) onsite parts replacement eight hours a day, five days a week.
- 90-day software warranty on media.
- Ongoing downloads of BIOS, drivers, and firmware updates.
- UCSM updates for systems with Unified Computing System Manager. These updates include minor enhancements and bug fixes that are designed to maintain the compliance of UCSM with published specifications, release notes, and industry standards.

SMARTnet for UCS

For support of the entire Unified Computing System, Cisco offers the Cisco SMARTnet for UCS Service. This service provides expert software and hardware support to help sustain performance and high availability of the unified computing environment. Access to Cisco Technical Assistance Center (TAC) is provided around the clock, from anywhere in the world.

For UCS blade servers, there is Smart Call Home, which provides proactive, embedded diagnostics and real-time alerts. For systems that include Unified Computing System Manager, the support service includes downloads of UCSM upgrades. The Cisco SMARTnet for UCS includes flexible hardware replacement options, including replacement in as little as two hours. There is also access to Cisco's extensive online technical resources to help maintain optimal efficiency and uptime of the unified computing environment. You can choose a desired service listed in [Table 10](#).

Table 10 Cisco SMARTnet for UCS Service

Product ID (PID)	On Site?	Description
CON-PREM-B230M2	Yes	ONSITE 24X7X2 B230 M2 Blade Server
CON-OSP-B230M2	Yes	ONSITE 24X7X4 B230 M2 Blade Server
CON-OSE-B230M2	Yes	ONSITE 8X5X4 B230 M2 Blade Server
CON-OS-B230M2	Yes	ONSITE 8X5XNBD B230 M2 Blade Server
CON-S2P-B230M2	No	SMARTNET 24X7X2 B230 M2 Blade Server
CON-SNTP-B230M2	No	SMARTNET 24X7X4 B230 M2 Blade Server
CON-SNTE-B230M2	No	SMARTNET 8X5X4 B230 M2 Blade Server
CON-SNT-B230M2	No	SMARTNET 8X5XNBD B230 M2 Blade Server

SMARTnet for UCS Hardware Only Service

For faster parts replacement than is provided with the standard Cisco Unified Computing System warranty, Cisco offers the Cisco SMARTnet for UCS Hardware Only Service. You can choose from two levels of advanced onsite parts replacement coverage in as little as four hours. SMARTnet for UCS Hardware Only Service provides remote access any time to Cisco support professionals who can determine if a return materials authorization (RMA) is required. You can choose a service listed in [Table 11](#).

Table 11 SMARTnet for UCS Hardware Only Service

Product ID (PID)	Service Level GSP	On Site?	Description
CON-UCW7-B230M2	UCW7	Yes	UC PLUS 24X7X4OS B230 M2 Blade Server
CON-UCW5-B230M2	UCW5	Yes	UC PLUS 8X5XNBDOS B230 M2 Blade Server

Unified Computing Partner Support Service

Cisco Partner Support Service (PSS) is a Cisco Collaborative Services service offering that is designed for partners to deliver their own branded support and managed services to enterprise customers. Cisco PSS provides partners with access to Cisco's support infrastructure and assets to help them:

- Expand their service portfolios to support the most complex network environments
- Lower delivery costs
- Deliver services that increase customer loyalty

Partner Unified Computing Support Options enable eligible Cisco partners to develop and consistently deliver high-value technical support that capitalizes on Cisco intellectual assets. This helps partners to realize higher margins and expand their practice.

PSS is available to all Cisco PSS partners, but requires additional specializations and requirements. For additional information, see the following URL:

www.cisco.com/go/partnerucssupport

The two Partner Unified Computing Support Options include:

- Partner Support Service for UCS
- Partner Support Service for UCS Hardware Only

Partner Support Service for UCS provides hardware and software support, including triage support for third party software, backed by Cisco technical resources and level three support. See [Table 12](#).

Table 12 Partner Support Service for UCS

Product ID (PID)	Service Level GSP	On Site?	Description
CON-PSJ1-B230M2	PSJ1	No	UCS SUPP PSS 8X5XNBD B230 M2 Blade Server
CON-PSJ2-B230M2	PSJ2	No	UCS SUPP PSS 8X5X4 B230 M2 Blade Server
CON-PSJ3-B230M2	PSJ3	No	UCS SUPP PSS 24X7X4 B230 M2 Blade Server
CON-PSJ4-B230M2	PSJ4	No	UCS SUPP PSS 24X7X2 B230 M2 Blade Server

Partner Support Service for UCS Hardware Only provides customers with replacement parts in as little as two hours. See [Table 13](#).

Table 13 Partner Support Service for UCS (Hardware Only)

Product ID (PID)	Service Level GSP	On Site?	Description
CON-PSW2-B230M2	PSW2	No	UCS W PL PSS 8X5X4 B230 M2 Blade Server
CON-PSW3-B230M2	PSW3	No	UCS W PL PSS 24X7X4 B230 M2 Blade Server
CON-PSW4-B230M2	PSW4	No	UCS W PL PSS 24X7X2 B230 M2 Blade Server

Unified Computing Combined Support Service

Combined Services makes it easier to purchase and manage required services under one contract. SMARTnet services for UCS help increase the availability of your vital data center infrastructure and realize the most value from your unified computing investment. The more benefits you realize from the Cisco Unified Computing System (Cisco UCS), the more important the technology becomes to your business. These services allow you to:

- Optimize the uptime, performance, and efficiency of your UCS
- Protect your vital business applications by rapidly identifying and addressing issues
- Strengthen in-house expertise through knowledge transfer and mentoring
- Improve operational efficiency by allowing UCS experts to augment your internal staff resources
- Enhance business agility by diagnosing potential issues before they affect your operations

You can choose a service listed in [Table 14](#).

Table 14 UCS Computing Combined Support Service

Product ID (PID)	Service Level GSP	On Site?	Description
CON-NCF2-B230M2	NCF2	No	CMB SPT SVC 24X7X2 B230 M2 Blade Server
CON-NCF2P-B230M2	NCF2P	Yes	CMB SPT SVC 24X7X2OS B230 M2 Blade Server
CON-NCF4P-B230M2	NCF4P	Yes	CMB SPT SVC 24X7X4OS B230 M2 Blade Server
CON-NCF4S-B230M2	NCF4S	Yes	CMB SPT SVC 8X5X4OS B230 M2 Blade Server
CON-NCFCS-B230M2	NCFCS	Yes	CMB SPT SVC 8X5XNBDOS B230 M2 Blade Server
CON-NCFE-B230M2	NCFE	No	CMB SPT SVC 8X5X4 B230 M2 Blade Server
CON-NCFP-B230M2	NCFP	No	CMB SPT SVC 24X7X4 B230 M2 Blade Server
CON-NCFT-B230M2	NCFT	No	CMB SPT SVC 8X5XNBD B230 M2 Blade Server

Unified Computing Drive Retention Service

With the Cisco Unified Computing Drive Retention (UCDR) Service, you can obtain a new disk drive in exchange for a faulty drive without returning the faulty drive. In exchange for a Cisco replacement drive, you provide a signed Certificate of Destruction (CoD) confirming that the drive has been removed from the system listed, is no longer in service, and has been destroyed.

Sophisticated data recovery techniques have made classified, proprietary, and confidential information vulnerable, even on malfunctioning disk drives. The UCDR service enables you to retain your drives and ensures that the sensitive data on those drives is not compromised, which reduces the risk of any potential liabilities. This service also enables you to comply with regulatory, local, and federal requirements.

If your company has a need to control confidential, classified, sensitive, or proprietary data, you might want to consider one of the Drive Retention Services listed in [Table 15](#).



NOTE: Cisco does not offer a certified drive destruction service as part of this service.

Table 15 Drive Retention Service Options

Service Description	Service Program Name	Service Level GSP	Service Level	Product ID (PID)
SMARTnet for UCS Service with Drive Retention	UCS DR	UCSD7	24x7x4 Onsite	CON-UCSD7-B230M2
		UCSD7	8x5xNBD Onsite	CON-UCSD5-B230M2

Table 15 Drive Retention Service Options (*continued*)

Service Description	Service Program Name	Service Level GSP	Service Level	Product ID (PID)
SMARTnet for UCS HW ONLY+Drive Retention	UCS HW+DR	UCWD7	24x7x4 Onsite	CON-UCWD7-B230M2
		UCWD5	8x5xNBD Onsite	CON-UCWD5-B230M2

For more service and support information, see the following URL:

http://www.cisco.com/en/US/services/ps2961/ps10312/Unified_Computing_Services_Overview.pdf

For a complete listing of available services for Cisco Unified Computing System, see this URL:

http://www.cisco.com/en/US/products/ps10312/serv_group_home.html

ORDER OPTIONAL KVM CABLE


The KVM cable provides a connection into the server, providing a DB9 serial connector, a VGA connector for a monitor, and dual USB 2.0 ports for a keyboard and mouse. With this cable, you can create a direct connection to the operating system and the BIOS running on the server.

The KVM cable ordering information is listed in [Table 16](#).

Table 16 KVM Cable

Product ID (PID)	PID Description
37-1016-01	KVM Cable

Figure 4 KVM Cable




1	Connector (to server front panel)	3	VGA connector (for a monitor)
2	DB-9 serial connector	4	Two-port USB 2.0 connector (for a mouse and keyboard)

SUPPLEMENTAL MATERIAL

Motherboard

A top view of the B230 M2 motherboard is shown in *Figure 5*.

Figure 5 B230 M2 Motherboard




1	DIMM slots	4	DIMM slots
2	CPU 1 and heat sink	5	Mezzanine adapter card connector
3	CPU 2 and heat sink	6	Diagnostic button

DIMM and CPU Layout

Each CPU controls four memory channels, as shown in *Figure 6*.

Figure 6 B230 M2 Memory Organization




32 DIMMS
 512 GB maximum memory
 4 memory channels per CPU,
 up to 4 DIMMs per channel

- CPU1: Channels A, B, C, and D
 - Bank 1 - B0, B1; D0, D1 (blue DIMM slots)
 - Bank 2 - B2, B3; D2, D3 (yellow DIMM slots)
 - Bank 3 - A0, A1; C0, C1 (white DIMM slots)
 - Bank 4 - A2, A3; C2, C3 (black DIMM slots)
- CPU2: Channels A, B, C, and D
 - Bank 1 - B0, B1; D0, D1 (blue DIMM slots)
 - Bank 2 - B2, B3; D2, D3 (yellow DIMM slots)
 - Bank 3 - A0, A1; C0, C1 (white DIMM slots)
 - Bank 4 - A2, A3; C2, C3 (black DIMM slots)

The DIMM and CPU physical layout is shown in *Figure 7*. CPU 1 is located on the upper half of the board and controls the upper DIMMs. CPU 2 is located on the lower half of the board and controls the lower DIMMs.

Figure 7 DIMM and CPU Layout



NOTE: DIMMs installed in slots for an absent CPU are not recognized.

Memory Population Recommendations

Table 17 shows the preferred order for installing upgrade DIMMs, and while other configurations may work, if problems arise, moving them to the preferred arrangement should help. Note that the bank installation order is Bank 1, Bank 3, Bank 2, Bank 4.

Table 17 Preferred DIMM Population Order

DIMMs per CPU	Numbered Slots ¹
2 (blue)	(B0, B1)
4 (blue)	(B0, B1) - (D0, D1)
8 (blue, white)	(B0, B1) - (D0, D1) - (A0, A1) - (C0, C1)
16 (blue, white, yellow, black)	(B0, B1) - (D0, D1) - (A0, A1) - (C0, C1) - (B2, B3) - (D2, D3) - (A2, A3) - (C2, C3)

Notes . . .

1. The slots inside the parentheses are electrically paired with each other, and should be populated with identically matched DIMMs that were ordered as a pair. Do not swap a paired DIMM with a DIMM that is not identical in manufacturer part number.

When considering the memory configuration of your server, you should observe the following:

- DIMMs within the blade server can be of a different size.
- Your selected CPU(s) can have some effect on performance. If two CPUs are used, they must both be of the same type.
- Performance degradation can result from the following:
 - Mixing DIMM sizes and densities within a pair is not allowed and both DIMMs in the pair will be logically removed from the memory array
 - Unevenly populating DIMMs between CPUs
 - Populating channels with an odd number of total ranks (for example, mixing single-rank and dual-rank DIMMs)
 - Using anything other than 16 or 32 DIMMs properly placed in the system

TECHNICAL SPECIFICATIONS

Dimensions and Weight

Table 18 UCS B200 M2 Dimensions and Weight¹

Parameter	Value
Height	1.95 in. (50 mm)
Width	8.00 in. (203 mm)
Depth	24.4 in. (620 mm)
Weight	18.0 lbs (8.16 kg)*

Notes . . .

1. The system weight given here is an estimate for a fully configured system and will vary depending on the number of CPUs, memory DIMMs, and other optional items.

Power Specifications

For configuration-specific power specifications, use the Cisco UCS Power Calculator at:
http://www.cisco.com/assets/cdc_content_elements/flash/dataCenter/cisco_ucs_power_calculator/.



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

Cisco and the Cisco Logo are trademarks of Cisco Systems, Inc. and/or its affiliates in the U.S. and other countries. A listing of Cisco's trademarks can be found at www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1005R)