QuickSpecs

HP 4Gb PCIe Fibre Channel Host Bus Adapters

Overview

The HP 4Gb PCI-Express Fibre Channel Host Bus Adapters (HBAs) support customers using HP ProLiant servers with PCIe I/O slots running a broad range of operating systems. These Fibre Channel HBAs are second generation products that support this new higher speed I/O bus architecture and provide customers the ability to use it to connect to their HP arrays.

For supported Fibre Channel SAN Switches, please consult the SAN Design Reference Guide at the following URL: http://h18006.www1.hp.com/products/storageworks/san/documentation.html

Models

		Part Number
Brocade	HP 41B 4Gb PCIe FC HBA	AP767B
	HP Single Channel 4Gb PCIe Fibre Channel Host Bus Adapter	
	HP 42B 4Gb Dual-Port PCIe FC HBA	AP768B
	HP Dual Channel 4Gb PCIe Fibre Channel Host Bus Adapter	
Emulex	HP FC2142SR	A8002B
	HP 42B 4Gb Dual-Port PCIe FC HBA	
	HP FC2242SR Dual Channel 4Gb PCIe HBA	A8003B
	HP Dual Channel 4Gb PCIe Fibre Channel Host Bus Adapter	
QLogic	HP FC1142SR 4Gb PCIe HBA	AE311A
-	HP Single Channel 4Gb PCIe Fibre Channel Host Bus Adapter	
	HP FC1242SR Dual Channel 4Gb PCIe HBA	AE312A
	HP Dual Channel 4Gb PCIe Fibre Channel Host Bus Adapter	

What's New

• New RoHS compliant HP 4Gb Fibre Channel HBAs

NOTE: Restriction of Hazardous Substances Directive or RoHS is a directive adopted by the European Union that restricts the use of certain hazardous materials in the manufacture of various types of electronic and electrical equipment. The RoHS compliant products with new part numbers listed in this document are functionally equivalent to the corresponding products with old part numbers and are fully interchangeable.



QuickSpecs

HP 4Gb PCIe Fibre Channel Host Bus Adapters

Overview

At A Glance

Industry leading PCI-Express based solutions for Fibre Channel

- Agility: Adds 4Gb PCI Express single and dual channel I/O connectivity to HP storage arrays.
- Throughput: 4 Gbps FC increases aggregate throughput rate to 800 MBps per channel in full-duplex mode.
- Performance: PCI-Express host bus interface for high throughput applications.
- High Transfer Rate: Minimum 150,000 IOPS per channel delivers high I/O transfer rates for storage applications.
- Management: Enterprise wide management capabilities.

Warranty

3-0-0 Three-year parts exchange warranty. Additional warranty protection can be purchased.

HP Global Services provides a three-year, limited warranty, fully supported by a worldwide network of resellers and service providers toll-free 7 x 24 hardware technical phone support for the duration of the warranty. In addition, available service offerings include a full range of HP Care Pack packaged hardware and software services.

NOTE: Certain restrictions and exclusions apply. Consult the HP Customer Support Center for details.



QuickSpecs

HP 4Gb PCIe Fibre Channel Host Bus Adapters

Service and Support, HP Care Pack, and Warranty Information

Service and Support Technology Services for increased uptime, productivity and ROI

TRUST HP storage technology experts for every level of service and support. Our integrated portfolio of Services for storage help customers reduce costs, optimize data, streamline storage management, and improve backup and recovery. Capitalizing on HP Storage Systems' capabilities requires a service partner who understands your increasingly complex environment. Team with the people who know HP infrastructure hardware and software best-the experienced professionals at HP Services.

Protect your business beyond warranty

Warranty protects against manufacturer defects, however warranty uplifts, such as HP Care Pack Services protect the business-by reducing downtime risks and providing operational consistency for mission-critical and standard business computing.

What HP Storage Technology Services can do for you

HP Storage Technology Services can help you design, deploy, test, integrate, support, and manage IT and infrastructure solutions. HP storage lifecycle support services offers a full spectrum of customer care-from technology support to complex migrations to complete managed services.

Choose the right level of support, deployment and integration services

Leverage the full strength of HP Technology Services - customers can trust the services professionals at HP to work collaboratively with them, putting our strategic and technical know-how to work across their entire infrastructure.

Support	 HP Host Bus Adapters (HBA) take on the support level of the HP server in which it is installed. For HBA s installed outside of an HP environment, HP Foundation Care 24x7 Service is recommended For a higher return on your storage investment, HP Support Plus 24 provides integrated hardware and software support services designed specifically for your technology. Available 24x7, this 3-year combined reactive support option delivers onsite hardware support and over-the-phone software support around-the-clock. Improve uptime with responsive hardware and software services Enjoy consistent service coverage across geographically dispersed sites Update HP software at a predictable cost Increase customer satisfaction-with no interoperability gaps
Installations	 HP Installation is included with the HP Server install if purchased together. If Host Bus Adapters (HBA) is ordered as an add-on to an existing HP Server or for installation into a non-HP Server, HP Installation Service is recommended. HP Hardware Installation provides basic installation of your product into your technology environment (System configuration is not included). Allows your IT resources to stay focused on their core tasks and priorities Reduces implementation time, impact and risk to your storage environment



QuickSpecs

HP 4Gb PCIe Fibre Channel Host Bus Adapters

Service and Support, HP Care Pack, and Warranty Information

RemoteHP Insight Remote Support-: Available at no additional cost to all warranty, HP Care Pack Service andSupport Toolsservice agreement customers, uses proven technology to deliver secure, reliable 24x7 remote monitoring,
diagnosis and problem resolution.

http://h20195.www2.hp.com/V2/GetPDF.aspx/4AA2-4676ENW.pdf

For more informationwww.hp.com/services/storageTo learn more on HP Storage Services, please contact your HP sales representative or HP Authorized
Channel Partner

HP Care Pack Services are sold by HP and HP Authorized Service Partners:

- Services for customers purchasing from HP or an enterprise reseller are quoted using HP order configuration tools.
- Customers purchasing from a commercial reseller can find HP Care Pack Services at www.hp.com/go/lookuptool



QuickSpecs

HP 4Gb PCIe Fibre Channel Host Bus Adapters

Technical Specifications

		Family Co	mparison Ta	ble		
	41B/AP767B	42B/AP768B	FC2142SR / A8002B	FC2242SR / A8003B	FC1142SR / AE311A	FC1242SR / AE312A
Number of channels	Single	Dual	Single	Dual	Single	Dual
Port Speed	4 Gbps	4 Gbps	4 Gbps	4 Gbps	4 Gbps	4 Gbps
Slot type supported	PCI Express to Fibre Channel	PCI Express to Fibre Channel	PCI Express to Fibre Channel	PCI Express to Fibre Channel	PCI Express to Fibre Channel	PCI Express to Fibre Channel
OS Supported NOTE: Always refer to the H specific product support inf	-	Connectivity Know	ledge for HP Stora	age Products at: w	ww.hp.com/stora	ge/spock for
Windows Server 2003	x86, x64, R2	x86, x64, R2	x86, x64, IA64, R2	x86, x64, IA64, R2	x86, x64, R2	x86, x64, IA64, R2
Windows Server 2008	x86, x64, R2	x86, x64, R2	x86, x64, IA64, R2	x86, x64, IA64, R2	x86, x64, R2	x86, x64, IA64, R2
VMware 3.5	U4/U5	U4/U5	U4/U5	U4/U5	U4/U5	U4/U5
VMware 4.0	YES	YES	YES	YES	YES	YES
VMware 4.1	YES	YES	YES	YES	YES	YES
RHEL 4	N/A	N/A	x86, x64, IA64	x86, x64, IA64	x86, x64	x86, x64, IA64
RHEL 5	x86, x64	x86, x64	x86, x64, IA64	x86, x64, IA64	x86, x64	x86, x64, IA64
SLES 10	x86, x64	x86, x64	x86, x64, IA64	x86, x64, IA64	x86, x64	x86, x64, IA64
SLES 11	x86, x64	x86, x64	x86, x64, IA64	x86, x64, IA64	x86, x64	x86, x64, IA64
Solaris 10 x86	N/A	N/A	x86	x86	x86	x86
	Always re	-		tivity Knowledge ecific product sup	-	oducts at:
Servers Supported	Select HP ProLiant G7, G6, and G5/G5p servers NOTE: Refer to server QuickSpecs for details regarding supported options.					
Array Platforms Supported	Refer to www.hp.com/storage/spock for specific product support information					
Environmental - Operating Temperature	32º to 122º F (0º to 50º C) (dry bulb)	32º to 122º F (0º to 50º C) (dry bulb)	32° to 113° F (0° to 45° C)	32° to 113° F (0° to 45° C)	32° to 131° F (0° to 55° C)	32° to 131° F (0° to 55° C)
Environmental - Storage Temperature	-40º F to 163º F (-43º to 73º C) (dry bulb)	-40º F to 163º F (-43º to 73º C) (dry bulb)	-4 ° to 158° F (-20° to 70° C)	-4 ° to 158° F (-20° to 70° C)	-20° to 158° F (-4° to 70° C)	-20° to 158° F (-4° to 70° C)
Environmental - Relative Humidity - Operating	5% to 93% (relative, non- condensing)	5% to 93% (relative, non- condensing)	5% to 95% non- condensing	5% to 95% non- condensing	5% to 95% non- condensing	10% to 90% non-condensing
Product Dimensions (HxW)	1.63 x 6.5 in (43 x 165 mm)	1.63 x 6.5 in (43 x 165 mm)	6.60 x 2.54 in (167.64mm x 64.4 mm)	6.60 x 2.54 in (167.64mm x 64.4 mm)	6.60 x 2.54 in (167.64 x 64.4 mm)	6.60 x 2.54 in (167.64 x 64.4 mm)
Media	Multi-mode Optic	Multi-mode Optic	Multi-mode Optic	Multi-mode Optic	Multi-mode Optic	Multi-mode Optic



QuickSpecs

HP 4Gb PCIe Fibre Channel Host Bus Adapters

Technical Specifications

Connector	Short wave laser with LC type connector					
Brackets	Shipped with					
	both ½ height					
	and full-height					
	brackets	brackets	brackets	brackets	brackets	brackets

© Copyright 2014 Hewlett-Packard Development Company, L.P.

The information contained herein is subject to change without notice.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

