

LSX1FAB10B1 Switching Fabric Module (JG623A/JH115A)

1 Card identifier

The mark LSX1FAB10B1 is printed at the upper left corner of the front panel, and is used to identify the card.

2 Specifications

Table 1 LSX1FAB10B1 specifications

Item	Specification
Processor	MIPS64 (Dual Core), 1GHz.
SDRAM	2GB DDR3 SDRAM.
Power consumption	135 W to 170 W.
Compatible device models	HPE FlexFabric 12910 Switch.

NOTE:

- To verify compatibility of the card with the software release you are using, see the release notes.
- Before you install the card to the switch, remove the protective box for the card.

When you install a switching fabric module, hold the ejector levers of the module with both hands, press the buttons on the ejector levers, and pull the ejector levers outward, and then press the ejector levers inward after the module is fully seated into the slot.

When you remove a switching fabric module, press the buttons on the ejector levers and pull the ejector levers outward, and then pull out the switching fabric module.

3 Obtaining documentation

For card installation, see the *HPE FlexFabric 12900 Switch Series Installation Guide*.

For software upgrade, see the *HPE FlexFabric 12900 Switch Series Software Upgrade Guide*.

To access documentation and support services, go to the Hewlett Packard Enterprise Support Center website:

www.hpe.com/support/hpesc



5998-4319R

The information in this document is subject to change without notice.

© Copyright 2016 Hewlett Packard Enterprise Development LP