



HPE OfficeConnect 1920S Switch Series - Spare Parts

[New model specific parts lists](#)

[HPE OfficeConnect 1920S 8G Switch \(JL380A\)](#)

[HPE OfficeConnect 1920S 24G 2SFP Switch \(JL381A\)](#)

[HPE OfficeConnect 1920S 48G 4SFP Switch \(JL382A\)](#)

[HPE OfficeConnect 1920S 8G Ppoe+ 65W Switch \(JL383A\)](#)

[HPE OfficeConnect 1920S 24G 2SFP Ppoe+ 185W Switch \(JL384A\)](#)

[HPE OfficeConnect 1920S 24G 2SFP Poe+ 370W Switch \(JL385A\)](#)

[HPE OfficeConnect 1920S 48G 4SFP Ppoe+ 370W Switch \(JL386A\)](#)

[Link to list of available documents](#)

New model specific parts lists

To look up RoHS-compliant information in PartSurfer, use the component's option part number or the sales order number for a system in which the component is used (available from the product QuickSpecs). [Click here to visit the HPE PartSurfer website](#) .

- The product Standard Models page now links the model SKU numbers to the spare parts list for each model found on the HPE PartSurfer web site. (To report missing or incorrect parts information in PartSurfer, please use the "Contact us" and "Missing or incorrect data" links within the PartSurfer web site utility.)
- To look up RoHS-compliant information in PartSurfer, use the component's option part number or the sales order number for a system in which the component is used (available in the QuickSpecs or Standard Models page).

[top](#)

HPE OfficeConnect 1920S 8G Switch (JL380A)

| Part Description | Spare Part Number |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|
| AC Adapter | |
| Universal Power Adapter | 5066-5563 |
| Accessory Kit | |
| Hub/Switch accessory kit - For wall or under table mounting - Includes three 3/4-inch (M4 20 mm long) screws, three wall anchors, and a cable tie for the power cord | 5066-0621 |
| Hub/Switch accessory kit - Half width - Includes four adhesive rubber feet, two rack mounting brackets, four rack mount screws (12-24 5/8-inch long), and eight screws (M4 8 mm long) to attach the mounting brackets | 5066-2232 |
| Adapter | |
| 13 W US wallmount adapter - DoE-6 | 5066-5562 |
| Power Cord | |
| Power cord OPT-954, 2 conductor - 1.8 m (6.0 ft) long | 8120-6314 |
| Power cord (Black) - 18 AWG, two conductor, 1.8 m (6.0 ft) long - Has straight (F) C7 receptacle (For 100 V ac in Japan) | 8120-6316 |
| Power cord (Black) - Two conductor, 1.8 m (6.0 ft) long - Has straight (F) C7 receptacle (For 220-230 V ac in South Africa) | 8120-6317 |
| Power cord OPT-950, 2 conductor - 1.8 m (6.0 ft) long | 8120-8367 |
| Power cord OPT-951, 2 conductor - 1.8 m (6.0 ft) long | 8120-8373 |
| Power cord (Black) - 18 AWG, two conductor, 1.8 m (6.0 ft) long - Has straight (F) C7 receptacle (For 220 V ac in Korea) | 8120-8441 |

| Part Description | Spare Part Number |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|
| Power cord OPT-955 - 2-cond 1.8 m (1.84 ft) long | 8120-8699 |
| Power cord OPT-952, 2 conductor - 1.8 m (6.0 ft) long | 8121-0514 |
| Power cord OPT-961, 2 conductor - 1.8 m (6.0 ft) long | 8121-0664 |
| Power cord (Black, Volex Z730966) - Two conductor, 1.8 m (6.0 ft) long - Has straight (F) C7 receptacle (For 230 V ac in India) | 8121-0702 |
| Power cord OPT-952, 2 conductor - 1.8 m (6.0 ft) long | 8121-0870 |
| Power cord (Black) - 18 AWG, two conductor, 1.8 m (6.0 ft) long - Has straight (F) C7 receptacle (For 110 V ac in Taiwan) | 8121-0963 |
| Power cord OPT-964, 2 conductor - 1.8 m (6.0 ft) long | 8121-1081 |
| Power Module | |
| AC power module (Plugs directly into the wall socket) - 13 watt power external module (100-240 V ac, 50-60 Hz nominal input and 12 V dc at 1.085 A maximum output) - Includes the adapter and DC cord to the device (For Continental Europe) | 5184-5864 |

[top](#)

HPE OfficeConnect 1920S 24G 2SFP Switch (JL381A)

| Part Description | Spare Part Number |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|
| Accessory Kit | |
| Rack mount / accessory kit - Includes two rack mounting brackets, eight 8-mm M4 screws to secure the brackets to the switch chassis, four 5/8-inch 12-24 rack mounting screws, and four rubber feet | 5069-6535 |
| Power Cord | |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 220 V ac in Argentina) | 8121-0729 |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 220 V in Europe) | 8121-0731 |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 220 V ac in Denmark) | 8121-0733 |
| Power cord (Black) - 18 AWG, three conductor, 2.3 m (7.5 ft) long - Has straight (F) C13 receptacle (For 220 V in Brazil and Thailand) | 8121-0734 |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 220 V in Chile) | 8121-0735 |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 240 V ac in India and South Africa) | 8121-0737 |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 220 V ac in Switzerland) | 8121-0738 |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 240 V in Singapore, Hong Kong and the U.K.) | 8121-0739 |
| Power cord (Black) - 18 AWG, three conductor, 2.5 m (8.2 ft) long - Has straight (F) C13 receptacle (For 230-240 V ac in Australia and New Zealand) | 8121-0837 |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 220V in China) | 8121-0943 |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 110 V ac in Taiwan) | 8121-0964 |
| Power cord (Flint Gray) - Three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 220 V ac in Israel) | 8121-1004 |
| Power cord (Black) - Three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 127 V ac in Brazil) | 8121-1071 |
| Power cord (Black) - Three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 120 V in the United States, Canada, and Mexico) | 8121-1141 |
| Power cord (Black) - Three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 100 V ac in Japan) | 8121-1143 |

[top](#)

HPE OfficeConnect 1920S 48G 4SFP Switch (JL382A)

| Part Description | Spare Part Number |
|------------------|-------------------|
|------------------|-------------------|

| Part Description | Spare Part Number |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|
| Accessory Kit | |
| Rack mount / accessory kit - Includes two rack mounting brackets, eight 8-mm M4 screws to secure the brackets to the switch chassis, four 5/8-inch 12-24 rack mounting screws, and four rubber feet | 5069-6535 |
| Power Cord | |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 220 V ac in Argentina) | 8121-0729 |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 220 V in Europe) | 8121-0731 |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.2 5ft) long - Has straight (F) C13 receptacle (For 220 V ac in Denmark) | 8121-0733 |
| Power cord (Black) - 18 AWG, three conductor, 2.3 m (7.5 ft) long - Has straight (F) C13 receptacle (For 220 V in Brazil and Thailand) | 8121-0734 |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 220 V in Chile) | 8121-0735 |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 240 V ac in India and South Africa) | 8121-0737 |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 220 V ac in Switzerland) | 8121-0738 |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 240 V in Singapore, Hong Kong and the U.K.) | 8121-0739 |
| Power cord (Black) - 18 AWG, three conductor, 2.5 m (8.2 ft) long - Has straight (F) C13 receptacle (For 230-240 V ac in Australia and New Zealand) | 8121-0837 |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 220V in China) | 8121-0943 |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 110 V ac in Taiwan) | 8121-0964 |
| Power cord (Flint Gray) - Three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 220 V ac in Israel) | 8121-1004 |
| Power cord (Black) - Three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 127 V ac in Brazil) | 8121-1071 |
| Power cord (Black) - Three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 120 V in the United States, Canada, and Mexico) | 8121-1141 |
| Power cord (Black) - Three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 100 V ac in Japan) | 8121-1143 |

[top](#)

HPE OfficeConnect 1920S 8G PPOE+ 65W Switch (JL383A)

| Part Description | Spare Part Number |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|
| Accessory Kit | |
| Hub/Switch accessory kit - Half width - Includes four adhesive rubber feet, two rack mounting brackets, four rack mount screws (12-24 5/8-inch long), and eight screws (M4 8 mm long) to attach the mounting brackets | 5066-2232 |
| Hub/Switch accessory kit - For wall or under table mounting - Includes three 3/4-inch (M4 20 mm long) screws, three wall anchors, and a cable tie for the power cord | 5066-0621 |
| Adapter | |
| 90 W, DoE-6 Adapter | 5066-5569 |
| Power Cord | |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 220 V ac in Argentina) | 8121-0729 |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 220 V in Europe) | 8121-0731 |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.2 5ft) long - Has straight (F) C13 receptacle (For 220 V ac in Denmark) | 8121-0733 |
| Power cord (Black) - 18 AWG, three conductor, 2.3 m (7.5 ft) long - Has straight (F) C13 receptacle (For 220 V in Brazil and Thailand) | 8121-0734 |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 220 V in Chile) | 8121-0735 |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 240 V ac in India and South Africa) | 8121-0737 |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 220 V ac in Switzerland) | 8121-0738 |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 240 V in Singapore, Hong Kong and the U.K.) | 8121-0739 |
| Power cord (Black) - 18 AWG, three conductor, 2.5 m (8.2 ft) long - Has straight (F) C13 receptacle (For 230-240 V ac in Australia and New Zealand) | 8121-0837 |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 220V in China) | 8121-0943 |

| Part Description | Spare Part Number |
|---------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 110 V ac in Taiwan) | 8121-0964 |
| Power cord (Flint Gray) - Three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 220 V ac in Israel) | 8121-1004 |
| Power cord (Black) - Three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 127 V ac in Brazil) | 8121-1071 |
| Power cord (Black) - Three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 120 V in the United States, Canada, and Mexico) | 8121-1141 |
| Power cord (Black) - Three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 100 V ac in Japan) | 8121-1143 |

[top](#)

HPE OfficeConnect 1920S 24G 2SFP Ppoe+ 185W Switch (JL384A)

| Part Description | Spare Part Number |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|
| Accessory Kit | |
| Rack mount / accessory kit - Includes two rack mounting brackets, eight 8-mm M4 screws to secure the brackets to the switch chassis, four 5/8-inch 12-24 rack mounting screws, and four rubber feet | 5069-6535 |
| Power Cord | |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 220 V ac in Argentina) | 8121-0729 |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 220 V in Europe) | 8121-0731 |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.2 5ft) long - Has straight (F) C13 receptacle (For 220 V ac in Denmark) | 8121-0733 |
| Power cord (Black) - 18 AWG, three conductor, 2.3 m (7.5 ft) long - Has straight (F) C13 receptacle (For 220 V in Brazil and Thailand) | 8121-0734 |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 220 V in Chile) | 8121-0735 |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 240 V ac in India and South Africa) | 8121-0737 |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 220 V ac in Switzerland) | 8121-0738 |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 240 V in Singapore, Hong Kong and the U.K.) | 8121-0739 |
| Power cord (Black) - 18 AWG, three conductor, 2.5 m (8.2 ft) long - Has straight (F) C13 receptacle (For 230-240 V ac in Australia and New Zealand) | 8121-0837 |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 220V in China) | 8121-0943 |
| Power cord (Black) - 18 AWG, three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 110 V ac in Taiwan) | 8121-0964 |
| Power cord (Flint Gray) - Three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 220 V ac in Israel) | 8121-1004 |
| Power cord (Black) - Three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 127 V ac in Brazil) | 8121-1071 |
| Power cord (Black) - Three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 120 V in the United States, Canada, and Mexico) | 8121-1141 |
| Power cord (Black) - Three conductor, 1.9 m (6.25 ft) long - Has straight (F) C13 receptacle (For 100 V ac in Japan) | 8121-1143 |

[top](#)

HPE OfficeConnect 1920S 24G 2SFP PoE+ 370W Switch (JL385A)

| Part Description | Spare Part Number |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|
| Accessory Kit | |
| Rack mount / accessory kit - Includes two front rack mount brackets, two wall/table mounting brackets, eight 8-mm M4 screws to secure the brackets to the switch chassis, four 5/8-inch 12-24 rack mounting screws, and four rubber feet | 5066-2231 |
| Power Cord | |
| Power cord - 3-wire, 2.5 m (8.2 ft) long - Has straight (F) C15 receptacle with a `U` shaped channel above the ground pin to prevent use of a lower rated power cord (For 120 V ac in the United States, Canada, and Mexico) | 8121-0914 |
| Power cord (Black) - 3-wire, 2.5 m (8.2 ft) long - Has straight (F) C15 receptacle with a `U` shaped channel above the ground pin to prevent use of a lower rated power cord (for 127 V ac in Brazil) | 8121-1265 |
| Power cord - 3-wire, 2.5 m (8.2 ft) long - Has straight (F) C15 receptacle with a `U` shaped channel above the ground pin to prevent use of a lower rated power cord (For 220V ac to 240V ac in the United Kingdom, Hong Kong, Singapore, and Malaysia) | 8121-1475 |

| Part Description | Spare Part Number |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|
| Power cord - 3-wire, 2.5 m (8.2 ft) long - Has straight (F) C15 receptacle with a `U` shaped channel above the ground pin to prevent use of a lower rated power cord (For 230/240 V ac in Australia and New Zealand) | 8121-1476 |
| Power cord - 3-wire, 2.5 m (8.2 ft) long - Has straight (F) C15 receptacle with a `U` shaped channel above the ground pin to prevent use of a lower rated power cord (For 220 V ac in Chile) | 8121-1477 |
| Power cord (Black) - 3-wire, 2.5 m (8.2 ft) long - Has straight (F) C15 receptacle with a `U` shaped channel above the ground pin to prevent use of a lower rated power cord (For 220 V ac in Israel) | 8121-1478 |
| Power cord - 3-wire, 2.5 m (8.2 ft) long - Has straight (F) C15 receptacle with a `U` shaped channel above the ground pin to prevent use of a lower rated power cord (For 220 V ac in Europe) | 8121-1479 |
| Power cord (Black) - 3-wire, 2.5 m (8.2 ft) long - Has straight (F) C15 receptacle with a `U` shaped channel above the ground pin to prevent use of a lower rated power cord (For 230 V ac in Switzerland) | 8121-1480 |
| Power cord - 3-wire, 2.5 m (8.2 ft) long - Has straight (F) C15 receptacle with a `U` shaped channel above the ground pin to prevent use of a lower rated power cord (For 220 V ac in Argentina) | 8121-1481 |
| Power cord three conductor, 2.5 m (8.2 ft) long, OPT-918 | 8121-1482 |
| Power cord (Black) - 3-wire, 2.5 m (8.2 ft) long - Has straight (F) C15 receptacle with a `U` shaped channel above the ground pin to prevent use of a lower rated power cord (For 230 V ac in India) | 8121-1483 |
| Power cord - 3-wire, 2.5 m (8.2 ft) long - Has straight (F) C15 receptacle with a `U` shaped channel above the ground pin to prevent use of a lower rated power cord (For 220 V ac in China) | 8121-1484 |
| Power cord - 3-wire, 2.5 m (8.2 ft) long - Has straight (F) C15 receptacle with a `U` shaped channel above the ground pin to prevent use of a lower rated power cord (For 220 V ac in Philippines and Thailand) | 8121-1485 |
| Power cord - 3-wire, 2.5 m (8.2 ft) long - Has straight (F) C15 receptacle with a `U` shaped channel above the ground pin to prevent use of a lower rated power cord (For 230 V ac in Denmark) | 8121-1486 |
| Power cord (Black) - 3-wire, 2.5 m (8.2 ft) long - Has straight (F) C15 receptacle with a `U` shaped channel above the ground pin to prevent use of a lower rated power cord (For 110 V ac in Taiwan) | 8121-1511 |
| Rack Mount Kit | |
| Rack mounting and accessory kit - Includes the two rack mount brackets, eight bracket to switch screws, four bracket to rack screws, cable tie (for power cord retention), and four rubber feet | 5092-0769 |

[top](#)

HPE OfficeConnect 1920S 48G 4SFP PPoE+ 370W Switch (JL386A)

| Part Description | Spare Part Number |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|
| Accessory Kit | |
| Rack mount / accessory kit - Includes two front rack mount brackets, two wall/table mounting brackets, eight 8-mm M4 screws to secure the brackets to the switch chassis, four 5/8-inch 12-24 rack mounting screws, and four rubber feet | 5066-2231 |
| Power Cord | |
| Power cord - 3-wire, 2.5 m (8.2 ft) long - Has straight (F) C15 receptacle with a `U` shaped channel above the ground pin to prevent use of a lower rated power cord (For 120 V ac in the United States, Canada, and Mexico) | 8121-0914 |
| Power cord (Black) - 3-wire, 2.5 m (8.2 ft) long - Has straight (F) C15 receptacle with a `U` shaped channel above the ground pin to prevent use of a lower rated power cord (for 127 V ac in Brazil) | 8121-1265 |
| Power cord - 3-wire, 2.5 m (8.2 ft) long - Has straight (F) C15 receptacle with a `U` shaped channel above the ground pin to prevent use of a lower rated power cord (For 220V ac to 240V ac in the United Kingdom, Hong Kong, Singapore, and Malaysia) | 8121-1475 |
| Power cord - 3-wire, 2.5 m (8.2 ft) long - Has straight (F) C15 receptacle with a `U` shaped channel above the ground pin to prevent use of a lower rated power cord (For 230/240 V ac in Australia and New Zealand) | 8121-1476 |
| Power cord - 3-wire, 2.5 m (8.2 ft) long - Has straight (F) C15 receptacle with a `U` shaped channel above the ground pin to prevent use of a lower rated power cord (For 220 V ac in Chile) | 8121-1477 |
| Power cord (Black) - 3-wire, 2.5 m (8.2 ft) long - Has straight (F) C15 receptacle with a `U` shaped channel above the ground pin to prevent use of a lower rated power cord (For 220 V ac in Israel) | 8121-1478 |
| Power cord - 3-wire, 2.5 m (8.2 ft) long - Has straight (F) C15 receptacle with a `U` shaped channel above the ground pin to prevent use of a lower rated power cord (For 220 V ac in Europe) | 8121-1479 |
| Power cord (Black) - 3-wire, 2.5 m (8.2 ft) long - Has straight (F) C15 receptacle with a `U` shaped channel above the ground pin to prevent use of a lower rated power cord (For 230 V ac in Switzerland) | 8121-1480 |
| Power cord - 3-wire, 2.5 m (8.2 ft) long - Has straight (F) C15 receptacle with a `U` shaped channel above the ground pin to prevent use of a lower rated power cord (For 220 V ac in Argentina) | 8121-1481 |
| Power cord three conductor, 2.5 m (8.2 ft) long, OPT-918 | 8121-1482 |

| Part Description | Spare Part Number |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| Power cord (Black) - 3-wire, 2.5 m (8.2 ft) long - Has straight (F) C15 receptacle with a `U` shaped channel above the ground pin to prevent use of a lower rated power cord (For 230 V ac in India) | 8121-1483 |
| Power cord - 3-wire, 2.5 m (8.2 ft) long - Has straight (F) C15 receptacle with a `U` shaped channel above the ground pin to prevent use of a lower rated power cord (For 220 V ac in China) | 8121-1484 |
| Power cord - 3-wire, 2.5 m (8.2 ft) long - Has straight (F) C15 receptacle with a `U` shaped channel above the ground pin to prevent use of a lower rated power cord (For 220 V ac in Philippines and Thailand) | 8121-1485 |
| Power cord - 3-wire, 2.5 m (8.2 ft) long - Has straight (F) C15 receptacle with a `U` shaped channel above the ground pin to prevent use of a lower rated power cord (For 230 V ac in Denmark) | 8121-1486 |
| Power cord (Black) - 3-wire, 2.5 m (8.2 ft) long - Has straight (F) C15 receptacle with a `U` shaped channel above the ground pin to prevent use of a lower rated power cord (For 110 V ac in Taiwan) | 8121-1511 |
| Rack Mount Kit | |
| Rack mounting and accessory kit - Includes the two rack mount brackets, eight bracket to switch screws, four bracket to rack screws, cable tie (for power cord retention), and four rubber feet | 5092-0769 |

[top](#)

Link to list of available documents

[Click here to view the list of documents available for HPE OfficeConnect 1920S Switch Series .](#)

[top](#)

©Copyright 2021 Hewlett Packard Enterprise Development LP

Hewlett Packard Enterprise Development shall not be liable for technical or editorial errors or omissions contained herein. The information provided is provided "as is" without warranty of any kind. To the extent permitted by law, neither HPE nor its affiliates, subcontractors or suppliers will be liable for incidental, special or consequential damages including downtime cost; lost profits; damages relating to the procurement of substitute products or services; or damages for loss of data, or software restoration. The information in this document is subject to change without notice. Hewlett Packard Enterprise Development and the names of Hewlett Packard Enterprise Development products referenced herein are trademarks of Hewlett Packard Enterprise Development in the United States and other countries. Other product and company names mentioned herein may be trademarks of their respective owners.